

Simon iO electronic DALI dimmer switch 230 V~ with slender rocker champagne Simon 270

REF. 21001316-094



BASIC INFORMATION

FINISH

Matt champagne

MATERIAL

Thermoplastic

PACKAGING CONTENTS

Dimmer switch and instruction sheet

SYMBOL

"+/-"

COMPATIBILITY

Simon 270 frames

ETIM CLASS

EC000025

REMARKS

Communication via Broadcast to ensure uniform configuration across all luminaires. It does not allow individual control of devices. No DALI source required.

TECHNICAL INFORMATION

AVAILABLE MARKET CE	IP RATING IP20	POWER SUPPLY (V~) 230 V~
CABLE SECTION ADMITTED (MM) From 1,5 to 2,5 mm	MAINTENANCE Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.	RAL 7048
NUMBER OF POSSIBLE ELEMENTS 1 element	TYPE OF MECHANISM Dimmer	STORAGE TEMPERATURE RANGE (°C) 0 - 35 °C
FREQUENCY 50 - 60 Hz	OPERATING TEMPERATURE RANGE (°C) 5 - 45 °C	VOLTAGE (V~) 127/230 V~
INDICATOR FUNCTION Yes		

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM) 7	INSTALLABLE IN FLUSH MOUNT JUNCTION BOX Universal	INSTALLATION TYPE Suitable for flush mounting
	INSTALLATION DIRECTION Horizontal	TYPE OF TERMINAL CONNECTION - FUNCTION 1 Screw

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | Dir. 2014/53/UE RED | EN 50428:2005 | EN 50428:2005 A1:2007 | EN 50428:2005 A2:2009 | EN IEC 63000:2018 | ETSI EN 300328 V2.2.2

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053286500

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8421053286500

PACKAGING VOLUME

249500.25

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

81

PACKAGING GROSS WEIGHT

0.082

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

55.5

PACKAGING NET WEIGHT

0.078

UNITARY PACKAGING GROSS
WEIGHT

0.078

PACKAGING LENGTH

55.5

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.078



Para información más detallada consultar la hoja de instrucciones
 For more detailed information check the instruction sheet