

Modular Lighting 729 60x60 4000K

REF. 72950033-884



BASIC INFORMATION

MATERIAL

Aluminium

APPLICATION

Office

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

POWER SUPPLY (V~)

220/240 V~

COLOR TYPE

NW

IP RATING

IP20

CONTROL

On/Off

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

50

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2014/30/UE EMC | Dir. 2009/125/EC ErP (Reg. UE 2019/2020) | Dir. 2009/125/EC ErP (Reg. UE 2019/2015) | Dir. 2011/65/UE RoHS + post. mod. | EN 60598-2-2:2012 | EN IEC 55015:2019 + A11:2020 | EN 62493:2015 | EN 61547:2009 | EN 62717:2017 + A2:2019 | EN IEC 61000-3-2:2019 + A1:2021*1 | EN IEC 63000:2018 | EN 61000-3-3:2013 + A1:2019 + A2:2021

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053305003

UNITARY PACKAGING HEIGHT

35

UNITARY PACKAGING WIDTH

62

UNITARY PACKAGING LENGTH

69

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

149730

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

2

PRODUCT NET WEIGHT

1.75

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053305003

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

0

PACKAGING WIDTH

0

PACKAGING LENGTH

0

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

0

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.75

PACKAGING WEIGHT UNIT

KGM