

LANE 1600 linear luminaire On/Off HO Surface-mounted 4000 K Asymmetric White

REF. 91301006-400



BASIC INFORMATION

BODY MATERIAL

Aluminium

PACKAGING CONTENTS

1 Unit

APPLICATION

Domestic,Office,Retail,Contract

ETIM CLASS

EC001743

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CRI

90

LIGHTING EFFICIENCY (LM/W)

hasta 97 lm/W

IP RATING

IP20

DIRECTIONAL

No

LUMENS (LM)

2513 lm

OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

DRIVER INCLUDED

Yes

NUMBER OF LUMINAIRES

1

POWER SUPPLY (V~)

220/240 V~

ELECTRICAL CLASS

I

MACADAM STEPS

<3 Step MacAdam

RAL

9016

ENERGY EFFICIENCY

A+

OPTICS

Asymmetric 56°

COLOR TEMPERATURE (K)

4000 K

L70 (°C)

100000h at 25°C

POWER FACTOR (Φ)

>0,8

CONTROL

On/Off

L90 (°C)

30000h at 25°C

POWER (W)

26 W

COLOR TYPE

CW

CHROMATICS CRI ICONS

CRI
90

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Surface-mounted/Suspended

REGULATIONS

EAC MARKED

No

ECORRAE MARKED

Yes

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8436547086436

PACKAGING VOLUME

16128000

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

80

PACKAGING GROSS WEIGHT

3.85

UNITARY PACKAGING GROSS WEIGHT

0

PACKAGING WIDTH

84

PACKAGING NET WEIGHT

3.5

PRODUCT NET WEIGHT

3.5

PACKAGING LENGTH

2400

PACKAGING WEIGHT UNIT

KGM