Aluminum trunking of 2m 90x55mm with 1 compartment for K45 functions

REF. **TK11081/8**



BASIC INFORMATION

DESCRIPTION

Aluminum channel with a length of 2m and a section of 90x55mm, featuring 1 front compartment capable of mounting all functions of the K45 range without the need for accessories, achieving significant time savings during installation. Regardless of the designed structure, it ensures the isolation of electrical wiring from voice, data, and multimedia, while maintaining its correct bending radius throughout the distribution. It adapts to different architectures through its installation accessories, with the possibility of branching to Mini Channel and Cable Guide via the pre-punched line. Made of high-quality anodized aluminum, it has an IP4X and IK07 protection rating. We are talking about a fire-retardant, self-extinguishing, and non-flame propagating material. The indicated price is per meter and is supplied in batches of 6 units (12 meters in total)

FINISH

Aluminium

COMPATIBILITY

Functions K45

MATERIAL

Aluminium

ETIM CLASS

EC001938

TECHNICAL INFORMATION

IK CLASSIFICATION
09

IP RATING
IP4X

KIT AVAILABILITY
No

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
Only with tool

REMOVAL OF COVER
No tools needed

REMOVAL OF THE FRAME
Only with tool

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053264201

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0

PRODUCT NET WEIGHT
1.316

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436043374

UNITS CONTAINED PACKAGING
12

PACKAGING HEIGHT
125

PACKAGING WIDTH
275

PACKAGING LENGTH
2020

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
69437500

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
15.792

PACKAGING WEIGHT UNIT
KGM