

Euro-American socket gloss black Simon 100

REF. 10000439-138



BASIC INFORMATION

FINISH

Gloss black

COMPATIBILITY

Frames Simon 100

ETIM CLASS

EC000125

TECHNICAL INFORMATION

AVAILABLE MARKET CE	CURRENT (A) 16 A	NOMINAL VOLTAGE (V~) 127/250 V~
CABLE SECTION ADMITTED (MM) From 1,5 to 2,5 mm	IP RATING IP20	OPERATING TEMPERATURE RANGE (°C) 0 - 40 °C
NUMBER OF POSSIBLE ELEMENTS 1 element	MAINTENANCE Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.	POWER SUPPLY (V~) 127/250 V~
FORMAT Euro-American	TYPE OF MECHANISM Insertion	STORAGE TEMPERATURE RANGE (°C) -25 - 75 °C
INDICATOR FUNCTION No	MONOBLOCK No	VERSION Unique

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM) 10	INSTALLABLE IN FLUSH MOUNT JUNCTION BOX universal	INSTALLATION TYPE Suitable for flush mounting
CLAW	INSTALLATION DIRECTION Horizontal, Vertical	TYPE OF TERMINAL CONNECTION - FUNCTION 1 Screw

REGULATIONS

REGULATIONS

IEC 60884-1 Ed 3.2 + NMX-J-412-1-ANCE 2011 + NMX-J-163-ANCE 2004 + IEC 60884-1 Ed 3.2 + NMX-J-412-1-ANCE 2011 + NMX-J-163-ANCE 2004

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING MEASUREMENT
UNIT
MMT

UNITARY PACKAGING WIDTH
0

PACKAGING EAN
8421053192283

PACKAGING VOLUME
1042800

UNITARY PACKAGING LENGTH
0

UNITS CONTAINED PACKAGING
5

PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING VOLUME
0

PACKAGING HEIGHT
75

PACKAGING GROSS WEIGHT
0.255

UNITARY PACKAGING GROSS
WEIGHT
0.026

PACKAGING WIDTH
88

PACKAGING NET WEIGHT
0.13

PRODUCT NET WEIGHT
0.026

PACKAGING LENGTH
158

PACKAGING WEIGHT UNIT
KGM

