

Bus coupling unit Scena

REF. 8900150-039



BASIC INFORMATION

COMPATIBILITY

Simon Scena

PACKAGING CONTENTS

Coupling unit and instructions

ETIM CLASS

EC000634

TECHNICAL INFORMATION

AVAILABLE MARKET CE	IP RATING IP20	RELATIVE HUMIDITY 20 to 85% (without condensation)
NUMBER OF POSSIBLE ELEMENTS 1 element	MAXIMUM VOLTAGE AT THE INPUT (VCC) 12 VCC	SOUND FEEDBACK Yes
INPUT CABLE SECTION ADMITTED (MM) 24 AWG 2 shielded twisted pairs with impedance of 120 Ohms	OPERATING TEMPERATURE RANGE (°C) 0 - 45 °C	STORAGE TEMPERATURE RANGE (°C) 25 - 70 °C
CURRENT (A) 75 mA	POWER SUPPLY (V~) 12 Vdc	VIBRATION FEEDBACK Yes
	PROTOCOL DMX-Scena	

INSTALLATION AND MAINTENANCE

BUS CABLE SECTION ADMITTED (MM) From 0.5 to 0.8 mm	CLAW Simon 27	INSTALLATION TYPE Suitable for surface and flush mounting
BUS CONNECTION TYPE OF TERMINAL CONNECTION Por inserción	INSTALLABLE IN FLUSH MOUNT JUNCTION BOX Universal	TYPE OF TERMINAL CONNECTION - FUNCTION 1 Screw

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + + EN 50581:2012 + EN 60669-2-5:2016

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053142585

PRODUCT NET WEIGHT

0.026

PACKAGING LENGTH

0

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

0

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053142585

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING NET WEIGHT

0.026

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

0

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS
WEIGHT

0.026

PACKAGING WIDTH

0

MECANISMOS SIMON 31, 75, 77, 82 Y 88

Mecanismos básicos / Basic switches



Interruptor unipolar / Single-pole switch
XXXX101-XXX



Interruptor unipolar / Single-pole switch
7700101-039



Pulsador / Push button switch
XXXX150-XXX



Pulsador / Push button switch
7700150-039



Interruptor bipolar / Double pole switch
XXXX133-XXX



Conmutador / 2-way switch
XXXX201-XXX



Conmutador / 2-way switch
7700201-039




Conmutador cruce / Intermediate switch
XXXX251-XXX



Conmutador cruce / Intermediate switch
7700251-039



Grupo 2 interruptores / 2 switches group
XXXX398-XXX



Pulsador desconexión / Push button disconnection switch
XXXX152-XXX



Grupo dos conmutadores / 2-way switches group
XXXX397-XXX



Grupo de pulsadores desconexión / Push button disconnection group
XXXX395-XXX



Grupo conmutador y pulsador / 2-way and push button switch group
XXXX301-XXX



Interruptor unipolar / Single-pole switch
XXXX102-XXX



Interruptor con piloto / Push button pilot switch
7700112-039



Interruptor bipolar / Double pole switch
XXXX134-XXX



Conmutador / 2-way switch
XXXX202-XXX



Interrupor unipolar con luminoso / Single-pole switch with light
XXXX104-XXX



Pulsador con luminoso / Push button switch with light
XXXX160-XXX



Pulsador con luminoso / Push button switch with light
7700160-039



Conmutador con luminoso / 2-way switch with light
XXXX204-XXX



Conmutador cruce con luminoso / Intermediate switch with light
XXXX254-XXX