

## On-desk set with 2 German socket outlets, 2 UPS sockets and plate for 2 RJ45 connectors aluminium Simon 400

REF. 42502220-133



## BASIC INFORMATION

### DESCRIPTION

With the kit of desk top full of Simon 400, will enjoy a greater number of functions in the same space, for its work area. Ideal for spaces co-working and meeting rooms, this kit consists of 2 Schuko socket outlets, 2 UPS (uninterruptable power supplies) and plate with 2 RJ45 connectors. Its compact design together with its finishes in aluminium, guaranteeing the integration of the set in the space, providing a current and minimalist style. Its power supply is connected to figure Wieland, it is compatible with a voltage of 250 V and current of 16 A, in addition, its dielectric strength is 2000 V at 50H / minute, without perforation does not contours and insulation resistance > 5 M $\Omega$  at 500 V. Manual elevation, its installation is designed to be flush mounted in furniture, does not require the use of additional tools and is carried out from the top of the table. Simplicity and speed that reduces the time of the assembly for the enjoyment of the product as soon as possible.

### FINISH

Aluminium

### MATERIAL

Metal

### COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

### PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

### ETIM CLASS

EC002759

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60°C

### FORMAT

Schuko

### HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

### INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

### CURRENT (A)

16 A

### IP RATING

IP30

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60°C

### TYPE OF POWER SUPPLY CONNECTOR

Wieland GST 18i male 3-pole overhead connector with 22 cm patch cord

### RAL

9006

### NUMBER OF RJ45 WINDOWS

2

### SNAP-FIT RJ45 PLATES

Keystone I, II and Systimax

### SNAP-FIT TYPE

Keystone I, II and Systimax

### NUMBER OF SOCKETS

2 sockets for standard current circuit and 2 sockets for stable current circuit (UPS)

### NUMBER OF UPS SOCKET OUTLETS

2

### VERSION

5 elements

### VOLTAGE (V~)

250 V~

## INSTALLATION AND MAINTENANCE

### CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

### EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

### TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

### INSTALLATION TYPE

Suitable for fixing to furniture.

### SECURING POSSIBILITIES

Using clips included in the fastening brackets

### MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50173-1:2011;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053195819

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

1.05

### PRODUCT NET WEIGHT

1.05

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053195819

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

300

### PACKAGING WIDTH

125

### PACKAGING LENGTH

95

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

3562500

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

1.05

### PACKAGING WEIGHT UNIT

KGM