

Luminaire S20 BT Mesh 15,7W 3000K with detector 8m HF+LUX aluminio IP65 IK10

REF. 89391603-163



BASIC INFORMATION

DESCRIPTION

Lighting fixture with integrated HF detector and Bluetooth connectivity. The power is 15.7, the luminous flux is 1209 and the color temperature is 3000 K.

The maximum installation height is 4m and the installation is surface-mounted. The detection range is 8m and the detection angle is 360°.

The brightness regulation range is 2 - 2000 lux and the timing range is 5 s - 15 min.

The configuration of the lighting fixture is done through a Bluetooth application. Possibility of interconnection between fixtures through Bluetooth mesh.

The power supply voltage is 220 - 240 VAC. The operating temperature is: -10 - 50 °C.

Protection grade IP 65 and IK 10 and dimensions: Ø 300 x 71 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

Aluminium

ETIM CLASS

EC002892

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP65

IK CLASSIFICATION

10

POWER SUPPLY (V~)

220/240 V~

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053404270

UNITARY PACKAGING GROSS WEIGHT

1.9

PACKAGING LENGTH

370

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

1.299

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2325323

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053404270

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

1.9

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

370

PACKAGING NET WEIGHT

1.299

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

150

PACKAGING WEIGHT UNIT

KGM