

Flush-mounted box for CIMA Classic installation for 2 double positions when installed in a plasterboard wall Simon

REF. SM260



BASIC INFORMATION

FINISH

Grey

MATERIAL

Plastic

COMPATIBILITY

With trim and flush-mounted wall frame of 2 double elements Simon Cima Classic.

ETIM CLASS

EC002601

TECHNICAL INFORMATION

HEAT RESISTANCE (°C)

+125 °C (in accordance with standard IEC 60695-10-2)

IK CLASSIFICATION

08

KIT AVAILABILITY

No

NUMBER OF PRE-PUNCHED HOLES 31 X 4.65MM

4

RAL

7011

RECESS DIMENSION (MM)

146 x 146 mm

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

INSTALLATION DIRECTION

Horizontal, Vertical

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436016163

PRODUCT NET WEIGHT

0.247

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

1474200

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8426436016163

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.25

UNITARY PACKAGING VOLUME

1474200

PACKAGING HEIGHT

63

PACKAGING NET WEIGHT

0.247

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

150

PACKAGING WEIGHT UNIT

KGM

UNITARY PACKAGING GROSS WEIGHT

0.247

PACKAGING LENGTH

156