

## German double socket outlet 16A 250V~ with safety device, LED and 1Click® terminal connection system graphite Simon 500 Cima

REF. 50010432-038



### BASIC INFORMATION

#### FINISH

Graphite

#### COMPATIBILITY

Simon 500 Cima enclosures

#### PACKAGING CONTENTS

Double socket outlet with cover,  
LED status indicator and  
installation manual

#### ETIM CLASS

EC000125

#### REMARKS

Possibility to order replacement cover in case of breakage, with article no.50001841-038

## TECHNICAL INFORMATION

### CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

### AVAILABLE IN

German and French format

### NUMBER OF CONNECTIONS PER TERMINAL

1 terminal connection for click terminal connection system and 2 terminal connections for screw terminal connection system

### DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

### FORMAT

Schuko

### HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

### INDICATOR FUNCTION

Yes

### INSULATION RESISTANCE (V-MΩ)

>5MΩ at 500V

### CURRENT (A)

16 A

### IP RATING

IP20

### KIT AVAILABILITY

Yes

### LED CONSUMPTION INDICATOR (mA)

0.55

### LINKABLE

Yes, using accessory 50000996-039

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 to 60 °C

### TYPE OF MECHANISM

Insertion

### NUMBER OF MODULES

2

### MONOBLOCK

No

### RAL

7021

### NUMBER OF SOCKETS

2

### VERSION

Double

### VOLTAGE (V~)

250 V~

## INSTALLATION AND MAINTENANCE

### CABLE STRIPPING NECESSARY (MM)

0

### REMOVAL OF COVER

Only with tool

### EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

### INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

### INSTALLATION DIRECTION

Vertical and horizontal

### INSTALLATION TYPE

Suitable for surface and flush mounting

### REMOVAL OF THE SOCKET

Only with tool

### TYPE OF TERMINAL CONNECTION - FUNCTION 1

1 click connection (1 click®)

### NUMBER OF TERMINALS

3 inputs and 3 outputs

## REGULATIONS

### REGULATIONS

Directive 2011/65/UE RoHS + EN 50581:2012 + IEC 60884-1 Ed. 3.2

## LOGISTICS INFORMATION

UNITARY EAN CODE 8421053254684	UNITARY PACKAGING WEIGHT UNIT KGM	UNITS CONTAINED PACKAGING 10
UNITARY PACKAGING GROSS WEIGHT 0.111	UNITARY PACKAGING WIDTH 0	PACKAGING MEASUREMENT UNIT MMT
UNITARY PACKAGING HEIGHT 0	PACKAGING EAN 8421053093399	PACKAGING VOLUME 3.525
UNITARY PACKAGING LENGTH 0	PACKAGING GROSS WEIGHT 0	PACKAGING VOLUME UNIT DMQ
PRODUCT NET WEIGHT 0.111	PACKAGING HEIGHT 112	PACKAGING WEIGHT UNIT KGM
UNITARY PACKAGING VOLUME 0	PACKAGING LENGTH 269	PACKAGING WIDTH 117
UNITARY PACKAGING VOLUME UNIT MMQ	PACKAGING NET WEIGHT 1.11	

