

Charger 5V DC via USB port type A and micro USB patch cord with cable winder white Simon K45

REF. K126A/9



BASIC INFORMATION

DESCRIPTION

The socket of load in white colour K126A / 9 of the series Simon K45 offers two modules that allow you to load the battery of 2 devices at the same time, it consists of a type A USB port 5 and a Micro-USB patch cord with a unique system to wind the wire automatically. With dimensions of 45x45 mm, the piece has been manufactured with metal components with halogen-free insulation and coated self-extinguishing thermoplastic of the best quality to ensure no flame spread in case of fire, if it had a fire, together with a minimum toxicity in case of smoke. Our collection Simon K45 presents the best solutions in compliance with the highest quality and security, and that is that our commitment is to offer our customers the best products adapted to each need. Trust/Confident in Simon to make your home a place safer.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

USB charger, trim cover with cable-winder, micro USB patch cord and installation manual

REMARKS

Allows simultaneous charging of a device connected through the type A USB connector and a device connected through the micro USB patch cord

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

1,5 A

TYPE OF MECHANISM

Insertion

CABLE SECTION ADMITTED (MM)

From 1,0 to 2,5 mm

IP RATING

IP20

NUMBER OF MODULES

2 modules

NUMBER OF CONNECTIONS PER TERMINAL

1 connection per terminal

KIT AVAILABILITY

No

MONOBLOCK

No

MAX TEMP DURING CONSTRUCTION WORK (°C)

0 a 45° C

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

RAL

9003

FORMAT

USB / Micro-USB

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 to 50° C

VERSION

Single

VOLTAGE (V~)

230 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

6

INSTALLATION DIRECTION

Vertical according to the direction of the mechanisms

REMOVAL OF THE SOCKET

Only with tool

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, specific Simon K45 and specific Simon 500 Cima using adaptor ref.50012088-030

INSTALLATION TYPE

Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

NUMBER OF TERMINALS

2 inputs

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60950-1:2006 + EN 60950-1:2006 A11:2009 + EN 60950-1:2006 A1:2010 + EN 60950-1:2006 A12:2011 + EN 60950-1:2006 A2:2013 + ETSI-EN 301489-34 V1.4.1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT	UNITARY PACKAGING WEIGHT	PACKAGING MEASUREMENT
0	UNIT	UNIT
	KGM	MMT
UNITARY PACKAGING WIDTH	PACKAGING EAN	PACKAGING VOLUME
0	8421053092491	0.329
UNITARY PACKAGING LENGTH	UNITS CONTAINED PACKAGING	PACKAGING VOLUME UNIT
0	1	DMQ
UNITARY PACKAGING VOLUME	PACKAGING HEIGHT	PACKAGING GROSS WEIGHT
0	57	0.086
UNITARY PACKAGING GROSS WEIGHT	PACKAGING WIDTH	PACKAGING NET WEIGHT
0.086	76	0.086
PRODUCT NET WEIGHT	PACKAGING LENGTH	PACKAGING WEIGHT UNIT
0.086	76	KGM