SUB-D25 connector (parallel port) female with trim plate white Simon K45

REF. **K104A/9**



BASIC INFORMATION

DESCRIPTION

The connections are increasingly important in our day-to-day life and, above all, in our work stations. We need to be quick and to achieve the best results in each occasion. At times, we need to that this information is swap so bidirectional and for this Simon brings us this SUB-D25 connector parallel port. It is a female connector with white trim plate in colour. It is composed of 2 elements and has 4 modules. It is a mechanism very versatile, since it can be placed both in surface-mounted and flush-mounted, while it is necessary to weld for the terminal connection. This connector for multimedia connections is part of the series K45. A series with countless combinations for your installations and with an objective firm: The supply to the spaces professionals from the best applications for workplace solutions on the market, always convenient, faster and safer.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Female SUB-D25 connector (parallel port)

ETIM CLASS

EC000018

REMARKS

Maximum wire length recommended; 30 meters For additional information, please read the product instruction sheet

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

CABLE SECTION ADMITTED (MM)
From 0,2 to 0,5 mm

CONNECTOR TYPE
Sub-D25

NUMBER OF CONTACTS
25

NUMBER OF POSSIBLE ELEMENTS
2 elements

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

OPERATING TEMPERATURE RANGE (°C)
5 - 40 °C

RAL
9003

STORAGE TEMPERATURE RANGE (°C)
-25 - 50 °C

VERSION
Single

NUMBER OF WIRES
25

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION TYPE
Suitable for surface and flush mounting

REGULATIONS

REGULATIONS
Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.038

PRODUCT NET WEIGHT
0.038

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436045446

UNITS CONTAINED PACKAGING
5

PACKAGING HEIGHT
70

PACKAGING WIDTH
93

PACKAGING LENGTH
140

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
911400

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.19

PACKAGING NET WEIGHT
0.19

PACKAGING WEIGHT UNIT
KGM