

## 880.31 Industrial Spotlight 4000 K ASYM

REF. 88031038-274



### BASIC INFORMATION

#### APPLICATION

Accent lighting, General lighting

#### PACKAGING CONTENTS

1 unit

#### ETIM CLASS

EC001744

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### CONTROL

On/Off

### LIGHTING EFFICIENCY (LM/W)

116 lm/W

### IK CLASSIFICATION

08

### CRI

70

### LUMENS (LM)

5800 lm

### IP RATING

IP65

### DIRECTIONAL

Yes

### LUMENS/W

5800lm/ 50W

### OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

### DRIVER INCLUDED

Yes

### OPTICS

Asymmetric

### POWER SUPPLY (V~)

100/240 V~

### L70 (°C)

100,000 h at 25 °C

### PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

### COLOR TEMPERATURE (K)

4000 K

### L90 (°C)

30,000 h at 25 °C

### POWER (W)

50 W

### COLOR TYPE

NW

## INSTALLATION AND MAINTENANCE

### INSTALLATION TYPE

Surface (with bracket)

## REGULATIONS

### WARRANTY

5 years

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053205457

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

2.472

### PRODUCT NET WEIGHT

2.287

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053205457

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

60

### PACKAGING WIDTH

355

### PACKAGING LENGTH

260

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

5538000

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

2.472

### PACKAGING NET WEIGHT

2.287

### PACKAGING WEIGHT UNIT

KGM