

PROFESSIONAL EXTENSIBLE 30M IP55 H07RN-F,3G2.5MM2 3 SOCKETS 16A 250V~ BLACK/RED SIMON

REF. EX922801



BASIC INFORMATION

DESCRIPTION

The professional Simon cable reel with 3 sockets IP55 and H07RN-F 3G2.5mm² cable of 30m is ideal for demanding outdoor work. It offers maximum protection against dust and water, great load capacity, and safety in industrial environments.

FINISH

Black/Red

APPLICATION

Professional

PACKAGING DIMENSIONS (MM)

300x208x380mm

MATERIAL

PVC

PACKAGING

Label

REMARKS

Professional extensible H07: With its highly resistant H07RN-F, 3G2.5mm² cable, it allows charging different electronic devices at the same time thanks to its 3 schuko sockets protected with a cover. IP55: Suitable for indoor and outdoor use. Protected against dust deposits and water jets from any angle. Ideal for indoor areas or outdoor places with limited exposure to water. Surge protection: It has a system to prevent overheating and includes a reset function. Extension of power sockets: Thanks to its 3G2.5 cable of 30m, you can connect all those devices that are further away from wall sockets. ON/OFF switch: You can turn off all sockets simultaneously and avoid extra or unnecessary energy consumption.

TECHNICAL INFORMATION

CURRENT (A)

16 A

MAXIMUM POWER (W)

3680

IP RATING

IP55

NOMINAL VOLTAGE (V~)

250 V~

REGULATIONS

WARRANTY

3 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8412852982090

UNITARY PACKAGING HEIGHT

380

UNITARY PACKAGING WIDTH

208

UNITARY PACKAGING LENGTH

300

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

12602520

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

8.208

PRODUCT NET WEIGHT

8.208

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

18412853010249

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

395

PACKAGING WIDTH

225

PACKAGING LENGTH

320

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

28440000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

8.208

PACKAGING NET WEIGHT

8.208

PACKAGING WEIGHT UNIT

KGM

simon

380 mm

208 mm

300 mm

