# Customisable kit with dual opening cover, brush, 4x USB charger, 6 schuko socket outlets and 4 empty elements white S400 Indesk Duo

REF. **46623000-130**



## BASIC INFORMATION

### DESCRIPTION

Among the flush-mounted devices in the Simon 400 Indesk Duo series, the customizable kit integrated into the table stands out, featuring a cover with two openings and a brush, a charger with 4 x USB ports, six schuko socket bases for standard current circuits, and four empty elements for personalization in white. Insulation resistance of >5 MO at 500 V, a current of 16 A, Wieland® gst18i connector with three aerial male poles with a 22 cm patch cord, voltage of 250 V~ and dielectric strength without perforation or contouring of 2000 V at 50 Hz for 1 minute are other of its characteristics. Why is this kit so resistant and safe? Because of the painted steel casing, anodized aluminum profile, covers and fastenings made of self-extinguishing thermoplastic and halogen-free materials with which its structure has been manufactured, materials that guarantee no flame propagation in case of fire and low toxicity in case of smoke emission.

### FINISH

White

### MATERIAL

Metal

### COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

### PACKAGING CONTENTS

Pre-wired profiles, enclosure, fastening claws, 3-pole T-branching with 1 male input and 2 female outputs and installation manual.

### ETIM CLASS

EC002759

# TECHNICAL INFORMATION

### AVAILABLE MARKET
CE

### PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
No

### PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Yes, thanks to the included protective cover and cable outlet with brush

### DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

### MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

### FORMAT
Schuko

### HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

### IK CLASSIFICATION
07

### INSULATION RESISTANCE (V-MΩ)
>5 MΩ a 500 V

### CURRENT (A)
16 A

### IP RATING
IP30

### MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

### NOMINAL VOLTAGE (V~)
250 V~

### OPERATING TEMPERATURE RANGE (°C)
-5...+60

### TYPE OF POWER SUPPLY CONNECTOR
Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

### RAL
9016

### NUMBER OF REAR ENTRANCES
4

### RECESS DIMENSION (MM)
318 x 175 mm (± 2mm)

### NUMBER OF SOCKETS
6 sockets for standard current circuit

### NUMBER OF USB CHARGERS
2

### VERSION
12 elements

## INSTALLATION AND MAINTENANCE

### CABLING ACCESS
With brush

### CLAW RANGE OF OPERATION (MM)
Between 20 and 40 mm

### NUMBER OF COVER OPENING POSITIONS
2

### EXTINGUISHING (ºC)
+70 ºC (according to standard IEC 60670)

### TYPE OF FASTENING
By tightening existing clamps in the fastening bracket.

### REMOVAL OF THE FRAME
Only with tool

### INSTALLATION TYPE
Suitable for recessed mount in furniture.

### OPENING ORIENTATION
At 45º and 135º

### SECURING POSSIBILITIES
Using supplied claws or screws in the available holes

### MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

## REGULATIONS

### REGULATIONS
Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

UNITARY EAN CODE
8421053273692

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
3.4

PRODUCT NET WEIGHT
3.4

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053273692

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
130

PACKAGING WIDTH
215

PACKAGING LENGTH
345

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
9642750

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
3.4

PACKAGING WEIGHT UNIT
KGM