

# Brightness sensor surface DALI-2 Input round white IP54

REF. 89262330-130



## BASIC INFORMATION

### DESCRIPTION

Surface-mounted round light intensity detector. The recommended installation height is 2.8 m, with a maximum height of 4 m. The light intensity regulation range is 2 - 1000 lux. The detector configuration is done through DALI. It has a TEACH operating mode. Possibility of interconnection between sensors via DALI. The control protocol is DALI-2 Input. The typical consumption is 6 mA. The power supply voltage is DALI (12 - 20.5 VDC). The operating temperature of the detector is: -20 - 50 °C. White finish, IP 54 protection rating, and dimensions: Ø 126 x 42 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

### FINISH

White

### COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

### ETIM CLASS

EC000189

## TECHNICAL INFORMATION

### IP RATING

IP54

### RAL

9003

### POWER SUPPLY (V~)

220/240 V~

### CONTROL

On/Off

## INSTALLATION AND MAINTENANCE

### MINIMUM INSTALLATION HEIGHT

2.3

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053401606

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING MEASUREMENT UNIT

MMT

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING VOLUME UNIT

MMQ

### UNITARY PACKAGING GROSS WEIGHT

0.234

### PRODUCT NET WEIGHT

0.145

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053401606

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

90

### PACKAGING WIDTH

124

### PACKAGING LENGTH

160

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

2325323

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0.234

### PACKAGING NET WEIGHT

0.145

### PACKAGING WEIGHT UNIT

KGM