

## Back kit for 2 elements with 1 two-way push-button switch, 1 USB charger and 1 Schuko socket outlet Simon 100

REF. 10010206-039



### BASIC INFORMATION

#### DESCRIPTION

This kit rear is part of the Simon 100 series and is designed as lighting point for two electrical elements of up to 16 A and 250 volts. On this occasion, the back kit is 2-way switch with a push button, a socket outlet base and a USB charger, so that stands out for its versatility and high functionality. The 2-way switch push button is ideal to allow the switching on the light from two different places, something common, for example, in bedrooms where it is located a system of switching on to the input of the room and other together with the headboard to increase the comfort of the user. It has a click terminal system, in the case of the plug and the 2-way switch, and screw for the USB. The operation is also very simple, consisting of a tilting push-button switch that facilitates interaction.

#### FINISH

Black

#### COMPATIBILITY

Front Kit Simon 100

#### ETIM CLASS

EC002846

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### IP RATING

IP20

### STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

### NUMBER OF POSSIBLE ELEMENTS

2 elements

### TYPE OF MECHANISM

Push button rocker switch/Insertion

### USB CHARACTERISTICS

10W

### FORMAT

Schuko,USB

### MONOBLOCK

No

### USB CURRENT (A)

2,1 A

### INDICATOR FUNCTION

No

### OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

### USB VOLTAGE (V~)

5 Vdc

### CURRENT (A)

10 AX

### POWER SUPPLY (V~)

250 V~

### VOLTAGE (V~)

250 V~

## INSTALLATION AND MAINTENANCE

### INSTALLATION DIRECTION

Horizontal

### KIT INSTALLATION DIRECTION

Horizontal

### TYPE OF TERMINAL CONNECTION - FUNCTION 2

USB: Screw

### INSTALLATION TYPE

Suitable for flush mounting

### TYPE OF TERMINAL CONNECTION - FUNCTION 1

Schuko/2-way Switch: 1 click connection (1 click®)

## REGULATIONS

### REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60950-1:2006 + EN 60950-1:2006 A11:2009 + EN 60950-1:2006 A1:2010 + EN 60950-1:2006 A12:2011 + EN 60950-1:2006 A2:2011\*3 + EN 60669-1:1999 + EN 60669-1:1999 A1:2002 + EN 60669-1:1999 A2: 2008\*2 + ETSI-EN 301489-34 v14.1\*3 + IEC 60884-1 Ed. 3.2\*1

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053147795

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

0.253

### PRODUCT NET WEIGHT

0.253

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053147795

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

75

### PACKAGING WIDTH

88

### PACKAGING LENGTH

158

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

1042800

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

252.8

### PACKAGING NET WEIGHT

0.253

### PACKAGING WEIGHT UNIT

GRM