Two-pole socket outlet 16A 250V~ with safety device and screw terminal connection white Simon 27 Play

REF. **27431-65**



BASIC INFORMATION

DESCRIPTION

Achieve maximum functionality in the minimum space with the two-pole socket outlet a white tones of the Simon 27 Play collection, with safety device child and screw terminal connection, this socket outlet linking the elegance of a sober lines, with the greatest and the most efficient functionality and innovation. Compatible with power supplies voltage of 250 Volts, and 16 Ampere current, has a size of 45 x 45 mm, with a cross-cable section supported 2.5 mm and stripping of 15 mm Manufactured with halogen-free thermoplastic and thermoset trim, guarantees the protection of the room in case of fire, as that prevents the flame spread and toxicity by smoke. It is designed for installation in recessed or surface-mounted, adapting to the needs of each space aesthetic and functional. Also, for greater versatility of the set, this two-pole socket outlet is compatible with the most common frames and mechanisms of the Simon 27 range.

FINISH

White

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Socket outlet with cover

ETIM CLASS

EC000125

REMARKS

The covers include a child-proof protective feature.

TECHNICAL INFORMATION

CABLE SECTION ADMITTED (MM)

2,5 mm

NUMBER OF POSSIBLE ELEMENTS

1 element

FORMAT

Two-pole

INDICATOR FUNCTION

No

CURRENT (A)

16 A

IP RATING

IP20

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TYPE OF MECHANISM

Insertion

MONOBLOCK

No

NOMINAL VOLTAGE (V~)

250 V~

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

VERSION

Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)
15

CLAW
Simon 27

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, American and Centralisations

INSTALLATION DIRECTION
Horizontal, Vertical

INSTALLATION TYPE
Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1
Screw

REGULATIONS

REGULATIONS
Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | UNE 20315-1-1:2017 | IEC 60884-1 Ed 3.2 | UNE 20315-1-2:2017

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053252079

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.045

PRODUCT NET WEIGHT
0.045

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053051481

UNITS CONTAINED PACKAGING
10

PACKAGING HEIGHT
53

PACKAGING WIDTH
105

PACKAGING LENGTH
221

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
1229865

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
0.45

PACKAGING WEIGHT UNIT
KGM