

2-way switch for card with 2 micro switch and light indicator 250V~ grey Simon 75

REF. 75550-35



BASIC INFORMATION

DESCRIPTION

This 2-way switch is suitable for cards and consists of 2 microswitches and a indicator light 6 A 250 V~. With grey finish, the mechanism consists of metal parts with halogen-free insulation and trim made of thermoplastic, a material known for its resistance to extreme temperatures, friction and knocks. It is advisable to install this 2-way switch in combination with a contactor / relay. This is not done, the maximum current of the 2-way switch is 6A (2A inductive). When to place the frame, the flanges of the frame should be broken. This control mechanism is included in the Simon 75 series, a collection that offers solutions suitable for all types of decorative spaces. To clean the 2-way switch, use a dry, soft textured cloth to avoid damaging the switch. Also, avoid cleaning products that are abrasive.

FINISH

Grey

PACKAGING CONTENTS

Mechanism and cover

COMPATIBILITY

Simon 75 frames

ETIM CLASS

EC001590

REMARKS

A contactor must be installed at the output of the mechanism. If this is not done, the maximum current of the switch is 10 A resistive (1.5 A inductive). It is recommended to protect the faston connectors with a heat shrink sleeve.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INDICATOR FUNCTION

Yes

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

CABLE SECTION ADMITTED (MM)

0,5 mm

CURRENT (A)

10 (1,5 ind.) A

POWER SUPPLY (V~)

250 V~

CONSUMPTION INDICATOR (mA)

1 mA

IP RATING

IP20

STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

FREQUENCY

50 Hz

TYPE OF MECHANISM

Card

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CLAW

Simon 27

INSTALLATION DIRECTION

Horizontal, Vertical

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Faston

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

INSTALLATION TYPE

Suitable for surface and flush mounting

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN IEC 61058-1:2018 | EN 61058-1-1:2016 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
1517738

UNITARY PACKAGING VOLUME
UNIT
MMQ

UNITARY PACKAGING GROSS
WEIGHT
0.08

PRODUCT NET WEIGHT
0.08

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING EAN
8421053048610

UNITS CONTAINED PACKAGING
5

PACKAGING HEIGHT
82

PACKAGING WIDTH
83

PACKAGING LENGTH
223

PACKAGING MEASUREMENT
UNIT
MMT

PACKAGING VOLUME
3017190

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.803

PACKAGING NET WEIGHT
0.4

PACKAGING WEIGHT UNIT
KGM