

## Downlight 800.21 White 15W 3000K DALI2

REF. 80021330-683



### BASIC INFORMATION

#### APPLICATION

General technical lighting

#### PACKAGING CONTENTS

1 Units

#### ETIM CLASS

EC001744

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### CRI

80

### LUMENS/W

1100 lm/15W

### IP RATING

IP54

### ELECTRICAL CLASS

tipo 2

### OPTICS

Extensive

### OPERATING TEMPERATURE RANGE (°C)

-15°C a 35°C

### L70 (°C)

50.000 h a 25°C

### PHOTOBIOLOGICAL CLASSIFICATION

Categoría exento

### POWER SUPPLY (V~)

220/240 V~

### LIGHT BEAM APERTURE ANGLE (°)

60°

### POWER (W)

15W

### COLOR TEMPERATURE (K)

3000K

### COLOR TYPE

WW

### SERVICE LIFE

50.000 h

### CONTROL

DALI2

### LIGHTING EFFICIENCY (LM/W)

80 lm/W

### COS $\Phi$

0.95

### LUMENS (LM)

1100 lm

## INSTALLATION AND MAINTENANCE

### MINIMUM INSTALLATION HEIGHT

80

### INSTALLATION TYPE

Recessed

### TYPE OF TERMINAL CONNECTION - FUNCTION 1

Quick connector

## REGULATIONS

### WARRANTY

5 years 50.000 h

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053304433

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

0.312

### PRODUCT NET WEIGHT

0.312

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053304433

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

110

### PACKAGING WIDTH

170

### PACKAGING LENGTH

175

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

3272500

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0.426

### PACKAGING NET WEIGHT

0.312

### PACKAGING WEIGHT UNIT

KGM