

## Plate for R/TV inductive sockets aluminium Simon 75

REF. 75053-33



### BASIC INFORMATION

#### DESCRIPTION

The innovation of the plate for R-TV + SAT inductive sockets Simon 75 graphite. It can be installed in 2 different ways, by surface mounting or flush mounting and you can also choose between the six finishes available that we put at your disposal. The most common temperature ranges of the plate for R-TV + SAT inductive sockets are 5 to 40° with a limit ranging from -25 to 50°. This type of plate applies UNE-EN 50083-2: 2013. The main manufacturing material is thermoplastic with a graphite plastic finish. The mechanism of the R-TV + SAT inductive sockets is of individual version, it does not contain any module but an element. This model includes R-TV + SAT engraving but not signaling function. For the correct maintenance of the plate for inductive sockets, it recommended to use a soft cloth slightly moistened in soapy water to clean it properly.

#### FINISH

Matt aluminium

#### MATERIAL

Thermoplastic,Aluminium

#### PACKAGING CONTENTS

Plate

#### SYMBOL

R-TV+SAT

#### COMPATIBILITY

Simon 75 mechanisms

#### ETIM CLASS

EC000018

#### REMARKS

Available in 6 finishes. It is recommended to choose a frame with a base the same colour as the rocker. (Only for replacement)

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### NUMBER OF POSSIBLE ELEMENTS

1 element

### FORMAT

R/TV

### INDICATOR FUNCTION

No

### IP RATING

IP20

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

### STORAGE TEMPERATURE RANGE (°C)

-25 - 50 °C

### VERSION

Single

## INSTALLATION AND MAINTENANCE

### INSTALLATION DIRECTION

Horizontal, Vertical

### INSTALLATION TYPE

Suitable for surface and flush mounting

## REGULATIONS

### REGULATIONS

Dir. 2014/30/UE EMC | Dir. 2011/65/UE RoHS + post. mod. | EN 50083-2:2012 | EN 50083-2:2012 A1:2015 | EN IEC 63000:2018

## LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.022

PACKAGING MEASUREMENT

UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT

UNIT

KGM

PACKAGING VOLUME

3026595

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053003121

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0

UNITS CONTAINED PACKAGING

10

PACKAGING GROSS WEIGHT

0.445

UNITARY PACKAGING VOLUME

UNIT

MMQ

PACKAGING HEIGHT

83

PACKAGING NET WEIGHT

0.22

UNITARY PACKAGING GROSS  
WEIGHT

0.022

PACKAGING WIDTH

165

PACKAGING WEIGHT UNIT

KGM

PACKAGING LENGTH

221