

Luminaire HOLE 25 Trimless 3000K Flood White CRI90

REF. 91420912-300



BASIC INFORMATION

FINISH

White

APPLICATION

Trimless

ETIM CLASS

EC001744

MATERIAL

Aluminium

PACKAGING CONTENTS

1 unit

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CRI

98

LUMENS (LM)

1330 lm

IP RATING

IP44

DRIVER INCLUDED

No

LUMENS/W

1330

OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

ELECTRICAL CLASS

Type 3

MACADAM STEPS

<3 Step MacAdam

POWER SUPPLY (V~)

11,3 V~

L70 (°C)

150.000h at 25°C

OPTICS

Flood 35°

RAL

9016

L90 (°C)

40.000h at 25°C

POWER (W)

20 W

COLOR TEMPERATURE (K)

2700 K

LIGHTING EFFICIENCY (LM/W)

103 lm/W

SERVICE LIFE

50.000 h

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Trimless

REGULATIONS

EAC MARKED

Yes

WARRANTY

5 years

REGULATIONS

Dir. 2009/125/EC ErP (Reg. UE 2019/2015) | Dir. 2009/125/EC ErP (Reg. UE 2019/2020) | Dir. 2011/65/UE RoHS + post. mod. | EN 62717:2017 + A2:2019 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8436547078578

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.26

PRODUCT NET WEIGHT

0.14

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8436547078578

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

50

PACKAGING WIDTH

85

PACKAGING LENGTH

190

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

807500

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.26

PACKAGING NET WEIGHT

0.14

PACKAGING WEIGHT UNIT

KGM