

PD-20x20 PIR+LUX SR superfacie DALI-2 Master white IP20

REF. 89212435-230



BASIC INFORMATION

DESCRIPTION

Surface PIR presence and brightness detector. The recommended installation height is 2.8 m, with a maximum height of 10 m. It has a detection angle of 360° and an opening angle of 180°. The tangential detection range is 20 x 20 m and the radial detection range is 8 x 8 m.

The brightness regulation range is 10 - 1000 lux and the timing range is 5 s - 60 min. The configuration of the detector is performed via remote control.

It features TEACH operating mode. Possibility of interconnection between sensors. The control protocol is DALI-2 Master. The number of dimmable luminaires via the DALI bus is 64 (3 groups).

The power supply voltage is 220 - 240 VAC. The operating temperature of the detector is: 0 - 40 °C.

White finish, protection rating IP 20 and dimensions: 120 x 120 x 65 mm.

5-year warranty

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

Yes

ETIM CLASS

EC000133

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

POWER SUPPLY (V~)

220/240 V~

CONTROL

DALI2 Master

IP RATING

IP20

RAL

9003

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053342428

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.386

PRODUCT NET WEIGHT

0.289

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053342428

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

160

PACKAGING WIDTH

100

PACKAGING LENGTH

140

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

2240000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.386

PACKAGING NET WEIGHT

0.289

PACKAGING WEIGHT UNIT

KGM