

## Downlight 706.21 Flush mount WW Wide Flood White

REF. 70621030-483



### BASIC INFORMATION

**APPLICATION**

Ambient lighting

**PACKAGING CONTENTS**

1 unit

**ETIM CLASS**

EC001744

## TECHNICAL INFORMATION

### FREQUENCY (HZ)

50 - 60 Hz

### DRIVER INCLUDED

Yes

### LUMENS/W

900 lm/15W

### IP RATING

IP44

### ELECTRICAL CLASS

Type 2

### OPTICS

Wide Flood

### OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

### INTEGRATED POWER SUPPLY

No

### PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

### POWER SUPPLY (V~)

100/240 V~

### L70 (°C)

30,000 h at 25 °C

### POWER (W)

15 W

### COLOR TEMPERATURE (K)

3100 K

### COLOR TYPE

WW

### POWER SUPPLY DIMENSIONS (MM)

45x141x26 mm

### CONTROL

On/Off

### LIGHTING EFFICIENCY (LM/W)

60 lm/W

### SERVICE LIFE

30.000 h


### CRI

80

### LUMENS (LM)

900 lm

### CHROMATICS CRI ICONS



## INSTALLATION AND MAINTENANCE

### MINIMUM INSTALLATION HEIGHT

180

### INSTALLATION TYPE

Flush mount

### TYPE OF TERMINAL CONNECTION - FUNCTION 1

Screw

## REGULATIONS

### WARRANTY

3 years 30,000 h

## LOGISTICS INFORMATION

UNITARY PACKAGING GROSS WEIGHT	UNITARY PACKAGING WIDTH	UNITS CONTAINED PACKAGING
0.528	0	1
UNITARY PACKAGING HEIGHT	PACKAGING EAN	PACKAGING MEASUREMENT UNIT
0	8421053121993	MMT
UNITARY PACKAGING LENGTH	PACKAGING GROSS WEIGHT	PACKAGING VOLUME
0	0.528	2.825
PRODUCT NET WEIGHT	PACKAGING HEIGHT	PACKAGING VOLUME UNIT
0.528	135	DMQ
UNITARY PACKAGING VOLUME	PACKAGING LENGTH	PACKAGING WEIGHT UNIT
0	155	KGM
UNITARY PACKAGING WEIGHT UNIT	PACKAGING NET WEIGHT	PACKAGING WIDTH
KGM	0.528	135