

Spotlight 880.32 industrial 4000 K SYM

REF. 88032038-174



BASIC INFORMATION

APPLICATION

Accent lighting, General lighting

PACKAGING CONTENTS

1 unit

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

CRI

70

LIGHTING EFFICIENCY (LM/W)

126 lm/W

IK CLASSIFICATION

08

DIRECTIONAL

Yes

LUMENS (LM)

12600 lm

IP RATING

IP65

DRIVER INCLUDED

Yes

LUMENS/W

12600lm/ 100W

OPERATING TEMPERATURE RANGE (°C)

40 °C maximum

L70 (°C)

100,000 h at 25 °C

OPTICS

Symmetric

POWER SUPPLY (V~)

100/240 V~

L90 (°C)

30,000 h at 25 °C

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

COLOR TEMPERATURE (K)

4000 K

LIGHT BEAM APERTURE ANGLE (°)

90°

POWER (W)

100 W

CONTROL

On/Off

COLOR TYPE

NW

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Surface (with bracket)

REGULATIONS

WARRANTY

5 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053205471

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

5.688

PRODUCT NET WEIGHT

4.14

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053205471

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

135

PACKAGING WIDTH

485

PACKAGING LENGTH

395

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

25862625

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

5.688

PACKAGING NET WEIGHT

4.14

PACKAGING WEIGHT UNIT

KGM