LANE 1200 linear luminaire On/Off LO Surface-mounted 2700 K Batwing Black

REF. **91300018-288**

BASIC INFORMATION

BODY MATERIAL	APPLICATION	PACKAGING CONTENTS
Aluminium	Domestic,Office,Retail,Contract	1 Unit

simon

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IP RATING
IP20

OPERATING TEMPERATURE RANGE (ºC)
0 - 35 ºC

POWER SUPPLY (V~)
220/240 V~

RAL
9005

COLOR TEMPERATURE (K)
2700 K

CONTROL
On/Off

CRI
90

CHROMATICS CRI ICONS

CRI
90

DIRECTIONAL
No

DRIVER INCLUDED
Yes

ELECTRICAL CLASS
I

ENERGY EFFICIENCY
A+

L70 (ºC)
100000h at 25ºC

L90 (ºC)
30000h at 25ºC

LIGHT BEAM APERTURE ANGLE (°)
105°

COLOR TYPE
WW

LIGHTING EFFICIENCY (LM/W)
hasta 97 lm/W

LUMENS (LM)
1900 lm

NUMBER OF LUMINAIRES
1

MACADAM STEPS
<3 Step MacAdam

OPTICS
Batwing 105°

POWER FACTOR (Φ)
>0,9

POWER (W)
28 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE
Surface-mounted/Suspended

REGULATIONS

EAC MARKED
No

ECORRAE MARKED
Yes

WARRANTY
5 years

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0

PRODUCT NET WEIGHT
3

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8436547045358

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
80

PACKAGING WIDTH
84

PACKAGING LENGTH
2400

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
16128000

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
3.3

PACKAGING NET WEIGHT
3

PACKAGING WEIGHT UNIT
KGM