

**Customisable kit with dual opening cover, brushes, 4xUSB
charger, 4 schuko socket outlets and 2 empty elements
black S400 Indesk Duo**

REF. 46422000-138



BASIC INFORMATION

DESCRIPTION

Private individuals and professionals already enjoy all the advantages of having the kit is part of the table customizable with two opening, brushes, charger 4xUSB and two gaps in black colour of the series Simon 400 Indesk Duo, range whose functions completes its installation, it is suitable to be flush mounted in furniture. This product has connector figure Wieland ® gst18i with 3 poles male in-line with patch cord of 22 cm, insulation resistance > 5 M Ω at 500 V and dielectric strength with no holes or contours with 2000 V at 50Hz during 1 minute. With 4 SCHUKO sockets for standard current circuit, has a current of 16 A and a voltage of 250 V ~. Also, has been designed with enclosure painted steel, profile in anodised aluminium, covers and fastenings in self-extinguishing thermoplastic and halogen-free, materials that prevent the flame spread in case of fire and low toxicity in the event of smoke generation.

FINISH

Black

MATERIAL

Metal

COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

PACKAGING CONTENTS

Pre-wired profiles, enclosure, fastening claws, 3-pole T-branching with 1 male input and 2 female outputs and installation manual.

ETIM CLASS

EC002759

REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the included protective cover and cable outlet with brush

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60  C

NUMBER OF POSSIBLE ELEMENTS

2

FORMAT

Schuko

HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

IK CLASSIFICATION

07

INSULATION RESISTANCE (V-MΩ)

>5 MΩ at 500 V

CURRENT (A)

16 A

IP RATING

IP30

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60  C

NOMINAL VOLTAGE (V~)

250 V~

OPERATING TEMPERATURE RANGE (°C)

-5...+60

TYPE OF POWER SUPPLY CONNECTOR

Wieland  GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL

9005

NUMBER OF REAR ENTRANCES

2

RECESS DIMENSION (MM)

228 x 175 mm (± 2mm)

NUMBER OF SOCKETS

4 sockets for standard current circuit

NUMBER OF USB CHARGERS

2

VERSION

8 elements

INSTALLATION AND MAINTENANCE

CABLING ACCESS

With brush

CLAW RANGE OF OPERATION (MM)

Between 20 and 40 mm

REMOVAL OF COMPONENTS

NUMBER OF COVER OPENING POSITIONS

2

EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

TYPE OF FASTENING

By lateral tightening of claws provided with the enclosure.

Optional possibility to fasten the enclosure with screws through the provided holes in the sides of the enclosure chassis.

REMOVAL OF THE FRAME

Only with tool

INSTALLATION TYPE

Suitable for recessed mount in furniture.

OPENING ORIENTATION

At 45° and 135°

REMOVAL OF THE PLATE

Only with tool

SECURING POSSIBILITIES

Using supplied claws or screws in the available holes

MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD; Directiva 2014/30/UE EMC; Directiva 2011/65/UE RoHS; EN 50173-1:2011; EN 50581:2012; EN 60670-1:2005; EN 60670-1:2005 A1:2013; EN 60950-1:2006; EN 60950-1:2006 A11:2009; EN 60950-1:2006 A1:2010; EN 60950-1:2006 A12:2011; EN 60950-1:2006 A2:2011*3; ETSI-EN 301489-34 V1.4.1; IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053197103

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

2.35

PRODUCT NET WEIGHT

2.35

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053197103

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

370

PACKAGING WIDTH

135

PACKAGING LENGTH

200

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

9990000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

2.35

PACKAGING WEIGHT UNIT

KGM