LOOP wall-mounted luminaire 3000 K Black

REF. **91229954-388**

BASIC INFORMATION

BODY MATERIAL	PACKAGING CONTENTS
Die-cast aluminium	1 Unit
APPLICATION	**PACKAGING DIMENSIONS (MM)**
Domestic,Office,Retail,Hotel,Contract	116x224x171 mm

TECHNICAL INFORMATION

IP RATING
IP20

OPERATING TEMPERATURE RANGE (ºC)
0 - 35 ºC

RAL
9005

COLOR TEMPERATURE (K)
3000 K

CRI
80

DIRECTIONAL
Yes

DRIVER INCLUDED
No

ELECTRICAL CLASS
II

ENERGY EFFICIENCY
A+

L70 (ºC)
20000h at 25ºC

LIGHT BEAM APERTURE ANGLE (°)
112º

COLOR TYPE
NW

LIGHTING EFFICIENCY (LM/W)
hasta 18 lm/W

LUMENS (LM)
77 lm

NUMBER OF LUMINAIRES
1

MACADAM STEPS
<3 Step MacAdam

OPTICS
General 112º

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE
Trimless

REGULATIONS

EAC MARKED
Yes

ECORRAE MARKED
No

WARRANTY
3 years

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.6

PRODUCT NET WEIGHT
0.35

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8436547041893

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
116

PACKAGING WIDTH
171

PACKAGING LENGTH
224

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
4627350

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.39

PACKAGING NET WEIGHT
0.35

PACKAGING WEIGHT UNIT
KGM