

Floodlight Home 2 13,7W 3000K with detector 10m 180° PIR+LUX white IP44

REF. 89193000-133



BASIC INFORMATION

DESCRIPTION

Projector with PIR detector. The power is 13.7 W, the luminous flux is 1150 lm, and the color temperature is 3000 K.

The maximum installation height is 4m and the installation is on wall (surface). The detection range is 10 m and the detection angle is 180 °.

The brightness regulation range is and the timing range is 8 s - 35 min.

The luminaire configuration is done through potentiometers.

The power supply voltage is 220 - 240 VAC. The operating temperature is: -20 - 40 °C.

Protection grade IP 44 and IK 03 and dimensions: 180 x 218 x 161 mm.

5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

ETIM CLASS

EC001744

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IP RATING

IP44

IK CLASSIFICATION

03

POWER SUPPLY (V~)

220/240 V~

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053356517

UNITARY PACKAGING GROSS WEIGHT

0.752

PACKAGING LENGTH

300

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.406

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

10800000

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053356517

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.752

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

300

PACKAGING NET WEIGHT

0.406

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

120

PACKAGING WEIGHT UNIT

KGM