

# ARCH Downlight X-Less Accessory Round 1 Network 1-10 V

REF. 91591019-999



## BASIC INFORMATION

### APPLICATION

Domestic, Office, Retail, Hotel, Contract

### PACKAGING DIMENSIONS (MM)

Ø115x169 mm

### PACKAGING CONTENTS

1 Unit

### ETIM CLASS

EC002556

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### CONTROL

1-10 V,Push Dim

### ENERGY EFFICIENCY

A+

### IP RATING

IP20 / IP43

### COS $\Phi$

0.94

### LIGHTING EFFICIENCY (LM/W)

111 lm/W

### OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

### DIRECTIONAL

No

### PHOTOBIOLOGICAL CLASSIFICATION

Class II

### POWER SUPPLY (V~)

220/240 V~

### DRIVER INCLUDED

No

### POWER FACTOR ( $\Phi$ )

> 0,55

### ELECTRICAL CLASS

II

## INSTALLATION AND MAINTENANCE

### INSTALLATION ALTERNATIVES

Flush-mounted, Surface-mounted

### INSTALLATION TYPE

Trimless

## REGULATIONS

### EAC MARKED

Yes

### ECORRAE MARKED

Yes

### WARRANTY

5 years

## LOGISTICS INFORMATION

UNITARY EAN CODE

8436547036677

UNITARY PACKAGING WEIGHT  
UNIT

KGM

PACKAGING MEASUREMENT  
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8436547036677

PACKAGING VOLUME

0.028

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

HLT

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

100

PACKAGING GROSS WEIGHT

0.44

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

160

PACKAGING NET WEIGHT

0.32

UNITARY PACKAGING GROSS  
WEIGHT

0.44

PACKAGING LENGTH

175

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.32