

Push-button switch with bell symbol 10A 250V~, built-in light and fast terminal connection system ivory Simon 31

REF. 31660-31



BASIC INFORMATION

DESCRIPTION

Push-button switch with bell engraving, 10 A current and 250V, built in LED system and quick terminal connection, in ivory colour and belonging to the series Simon 31. It works by tilting and can be combined with the reference 31802.31 in case of replacement of the indicator light and, in addition, it has 2 modules and supports a wire cross section of 1.5 to 2.5 mm, with a stripping of 11 mm, approximately. In addition, it can be installed on surfaces with a temperature located between 5 and 40°C, approximately, although it can withstand extreme temperatures of -25 to 50°C, approximately. Its dimensions are 64x65mm and complies with the European standards and regulations UNE -s 60669-1: 2002 + A1: 2003 + A2: 2009 standards, in addition to being manufactured with metal components with halogen-free insulation and thermoplastic trim. To clean it, it will only need to use a soft and dry cloth, slightly dampened in soapy water and never use abrasive cloths or cleaners that contain chlorine in its formula.

FINISH

Ivory

COMPATIBILITY

Simon 31 frames

ETIM CLASS

EC000029

MATERIAL

Thermoplastic

PACKAGING CONTENTS

Mechanism with rocker

REMARKS

Can be combined with article 31802-31 if replacing the light indicator.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

INDICATOR FUNCTION

Yes

TYPE OF MECHANISM

Pivoting

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

IP RATING

IP20

NOMINAL VOLTAGE (V~)

250 V~

CONSUMPTION INDICATOR (mA)

1 mA

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

OPERATING TEMPERATURE RANGE (°C)

5 - 40 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

VERSION

Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

11

INSTALLATION TYPE

Suitable for surface and flush mounting

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

REGULATIONS

REGULATIONS

UNE-EN 60669-1:2002 + A1:2003 + A2:2009

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

PACKAGING EAN

8421053007402

PACKAGING VOLUME

3026595

UNITARY PACKAGING LENGTH

0

UNITS CONTAINED PACKAGING

10

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

83

PACKAGING GROSS WEIGHT

0.91

UNITARY PACKAGING GROSS WEIGHT

0.091

PACKAGING WIDTH

165

PACKAGING NET WEIGHT

0.91

PRODUCT NET WEIGHT

0.091

PACKAGING LENGTH

221

PACKAGING WEIGHT UNIT

KGM