

Switch for blinds 10A 250V~ with 3 positions: up, down and stop white Simon 27 Play

REF. 27333-65



BASIC INFORMATION

DESCRIPTION

Switch for roller shutters with 10 A current and a power of 250 V~ with three available positions: Raise, lower and stop. Its finish is white in colour and you can find the element in the "Blind control" category of the Simon 27 Play series, its operation is tilting and the type is mechanical latching. As mentioned above, the mechanism is equipped with a control unit position to stop the rise / fall of the blind. Benefit from the best and most innovative electronic functions in addition to imposing the socket of the collection Simon 27 Play in every corner of your home, enjoy decorating is the key premise of the collection, which is why it brings a revolutionary concept that allows you to take the initiative in the decoration of each one of the corners of your home, making the most of each of its features in customization.

FINISH

White

COMPATIBILITY

Simon 27 Play, Simon 27 Neos, Simon 27 Scudo, Simon 27, Simon 27 Centralisations and Simon 44 Aqua frames

PACKAGING CONTENTS

Mechanism with rocker

ETIM CLASS

EC000044

REMARKS

Mechanism with centre position to stop the up/down movement of the blinds.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CURRENT (A)

10 A

TYPE OF MECHANISM

Pivoting

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

IP RATING

IP20

OPERATING TEMPERATURE

RANGE (°C)

5 - 40 °C

NUMBER OF POSSIBLE ELEMENTS

1 element

LATCH TYPE

Mechanical

STORAGE TEMPERATURE RANGE

(°C)

-25 - 50 °C

INDICATOR FUNCTION

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

VERSION

Single

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

11

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Universal, American and Centralisations

INSTALLATION TYPE

Suitable for surface and flush mounting

CLAW

Simon 27

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

Fast

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD | Dir. 2011/65/UE RoHS + post. mod. | EN 60669-1:2018 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053252017

UNITARY PACKAGING HEIGHT

22.8

UNITARY PACKAGING WIDTH

39.2

UNITARY PACKAGING LENGTH

46

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0.026

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.035

PRODUCT NET WEIGHT

0.035

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053080832

UNITS CONTAINED PACKAGING

10

PACKAGING HEIGHT

50

PACKAGING WIDTH

105.4

PACKAGING LENGTH

220

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1.159

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0.336

PACKAGING NET WEIGHT

0.35

PACKAGING WEIGHT UNIT

KGM