

**Aluminium mini column with 1 side for 4 elements graphite
Simon 500 Cima**

REF. 52550112-033



BASIC INFORMATION

DESCRIPTION

Anodised aluminium mini column for 1 side suitable for 4 elements with a graphite finish, this mechanism is included in the Simon 500 Cima series and measures 304 x 110 x 72 mm. It is an article in compliance with the current regulations and is also suitable for installation in any type of floor. It doesn't matter which this is raised or concrete. Thanks to the shape of the baseboard, it is possible to integrate the mini column to the floor trunking 85x18 mm. Maintenance is essential in this type of products, as this will give a greater durability. To do this, just clean the piece with a soft, dry cloth and avoid abrasive cleaners containing chlorine. The collection Simon 500 Cima is a series that aims to provide maximum workplace solutions to the work stations. This mechanism is a good example of this.

FINISH

Aluminium

MATERIAL

Aluminium

COMPATIBILITY

Simon 500 Cima and Simon 27 Play/Simon K45 mechanisms (using an adaptor)

PACKAGING CONTENTS

Mini column, baseboard, lower and upper trim, non-slip adhesive foam, fixing studs, ground connection cable, screws and installation manual

ETIM CLASS

EC001941

REMARKS

The shape of the baseboard allows integration of the mini column with the 85 x 18 mm floor trunking

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the inclusion of protective foam

AVAILABLE IN

1 and 2 sides

MAX TEMP DURING CONSTRUCTION WORK (°C)

+120 °C

EARTHING RESISTANCE

< 0.05 Ohms

ELECTRICAL PROPERTIES

With electrical continuity

ELECTROMAGNETIC IMMUNITY FOR VDM WIRING

Constant clearance between electric wiring and Voice, Data and Multimedia cables, eliminating electromagnetic interference and possible transmission errors.

IP RATING

IP4X

KIT AVAILABILITY

No

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 to +120 °C

NUMBER OF MODULES

4

VERSION

1 side

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS

Only with tool

TYPE OF FASTENING

Using the screws supplied

INSTALLATION DIRECTION

Vertical

INSTALLATION TYPE

Suitable for installing in any floor type, raised or concrete

SCREWS REQUIRED FOR FLOOR FIXING

4

REMOVAL OF TRIM FRAMES

Only with tool

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + EN 50085-2-4:2009

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053094358

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

1.26

PRODUCT NET WEIGHT

1.26

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053094358

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

85

PACKAGING WIDTH

128

PACKAGING LENGTH

867

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

9432960

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.26

PACKAGING WEIGHT UNIT

KGM

