Downlight 703.22 Square Comfort WW Spot Black

REF. **70322038-283**



BASIC INFORMATION

APPLICATION	PACKAGING CONTENTS	ETIM CLASS
Hotel,Restaurants,Residential,Retail,Office,Healthcare,Education	1 Unit	EC001744

TECHNICAL INFORMATION

FREQUENCY
50 - 60 Hz

IP RATING
IP44

OPERATING TEMPERATURE RANGE (°C)
15 - 35 °C

POWER SUPPLY (V~)
230 V~

COLOR TEMPERATURE (K)
3000 K

CONTROL
On/Off

CRI
80

CHROMATICS CRI ICONS

CRI
80

CUT OFF
No

DRIVER INCLUDED
Yes

L70 (°C)
30,000 h at 25 °C

LIGHT BEAM APERTURE ANGLE (°)
20°

COLOR TYPE
WW

LIGHTING EFFICIENCY (LM/W)
84 lm/W

LUMENS (LM)
630 lm

LUMENS/W
630 lm/7.5 W

OPTICS
Spot

PHOTOBIOLOGICAL CLASSIFICATION
Exempt category

POWER (W)
7.5 W

SERVICE LIFE
30.000 h

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE
Flush-mount

REGULATIONS

WARRANTY
3 years

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053088623

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.345

PRODUCT NET WEIGHT
0.225

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053088623

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
110

PACKAGING WIDTH
135

PACKAGING LENGTH
170

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
2524500

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.345

PACKAGING NET WEIGHT
0.225

PACKAGING WEIGHT UNIT
KGM