Voice and data flat plate for 1 element without dust cover for 1 Infra+® RJ45 connector white Simon K45

REF. **K075/9**



BASIC INFORMATION

DESCRIPTION

This is the flat data and voice plate, in a beautiful and versatile finished in white colour, series Simon K45. It has no dust shutter and is an element for an RJ45 connector, Infra +. In total is available for both one as for two RJ45 connectors. This one, in particular, is the individual version, half an element. To combine this plate of voice and data Simon in vertical enclosures (Teleblock, columns, etc.), it is necessary to 90 ° positioner resorting to the reference (: K66). In this way it is possible to guide the plate in vertical. Its exact dimensions are 45 x 45 millimetres and 8.5 millimetres of depth. The manufacturing materials of this plate Simon K45 are thermoplastic components, insulation, which prevent the propagation of the flame in case of fire. Also, to minimize the toxicity if there is smoke. It should be pointed out that it can be installed both on the surface-mounted and flush mounted. For proper maintenance, you just need to clean the plate with a soft cotton, very soft and completely dry cloth.

FINISH

White

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-030)

PACKAGING CONTENTS

Flat voice and data plate without dust cover

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90º positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

COMPATIBLE WITH CONNECTORS
Infra+® RJ45 connectors.

RJ45 CONNECTORS
Not included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

DUST PROTECTION
No

FORMAT
RJ45

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

NUMBER OF MODULES
Half

PLATE TYPE
Flat

RAL
9003

RJ45 ADAPTOR MODULE
Included in voice and data plate

SNAP-FIT RJ45 PLATES
Infra+® RJ45 connectors

SNAP-FIT TYPE
Infra+® RJ45 connectors

VERSION
Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-030)

INSTALLATION DIRECTION
Vertical according to the direction of the mechanisms

INSTALLATION TYPE
Suitable for surface and flush mounting

REMOVAL OF THE PLATE
Only with tool

REGULATIONS

REGULATIONS
Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.013

PRODUCT NET WEIGHT
0.013

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436025134

UNITS CONTAINED PACKAGING
20

PACKAGING HEIGHT
70

PACKAGING WIDTH
93

PACKAGING LENGTH
140

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
911400

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.22

PACKAGING NET WEIGHT
0.26

PACKAGING WEIGHT UNIT
KGM