Complete table-top kit with 4 German socket outlets and plate for 2 RJ45 connectors aluminium Simon 400

REF. **42504020-133**



BASIC INFORMATION

DESCRIPTION

Adapted to the new decorative trends, the kit of desk top in aluminium of the collection of Simon 400, provides the maximum functionality of connection for working areas in a compact design of minimalist style, ideal for co-working spaces, this kit consists of 4 Schuko socket outlets and a plate with 2 RJ45 connectors, compatible with Keystone I and II ports. Its compact design of 250 x 120 x 80 mm and its installation flush mounted without the need for additional tools, make this kit in the perfect solution to optimise the space, getting in technical performance. With a voltage of 250 V of power and 16 A of intensity, is connected to figure Wieland and has insulation resistance > 5 M? at 500 V and dielectric strength of 2000 V at 50H per minute. With the anodised aluminium and halogen-free thermoplastic as the raw materials, protecting the room in case of fire, to prevent the flame spread and toxicity by smoke.

FINISH

Aluminium

MATERIAL

Metal

COMPATIBILITY

Can be combined with the range of Electric Cabling from Simon.

PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

DIELECTRIC STRENGTH
No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60°C

FORMAT
Schuko

HEAT RESISTANCE (°C)
+70°C (according to standard IEC 60670)

INSULATION RESISTANCE (V-MΩ)
>5 M? at 500 V

CURRENT (A)
16 A

IP RATING
IP30

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 at +60° C

NOMINAL VOLTAGE (V~)
250 V~

TYPE OF POWER SUPPLY CONNECTOR
Wieland® GST 18i male 3-pole overhead connector with 22 cm patch cord

RAL
9006

NUMBER OF RJ45 WINDOWS
2

SNAP-FIT RJ45 PLATES
Keystone® I, II and Systimax®

SNAP-FIT TYPE
Keystone® I, II and Systimax®

NUMBER OF SOCKETS
4 sockets for standard current circuit

VERSION
5 elements

INSTALLATION AND MAINTENANCE

CLAW RANGE OF OPERATION (MM)
Between 16 and 40 mm

EXTINGUISHING (°C)
+70 °C (according to standard IEC 60670)

TYPE OF FASTENING
By tightening existing clamps in the fastening bracket.

INSTALLATION TYPE
Suitable for fixing to furniture.

SECURING POSSIBILITIES
Using clips included in the fastening brackets

MOUNTING WITHOUT ACCESSORIES
Supplied with all necessary materials for installation.

REGULATIONS

REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50173-1:2011;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053195901

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS WEIGHT
0.835

PRODUCT NET WEIGHT
0.835

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053195901

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
90

PACKAGING WIDTH
116

PACKAGING LENGTH
298

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3111120

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
0.835

PACKAGING WEIGHT UNIT
KGM