

Watertight luminaire 789 36W 5500K 1200

REF. 78937033-885



BASIC INFORMATION

DESCRIPTION

Waterproof luminaire for parking, garage, and technical area applications, designed to provide uniform and comfortable lighting in circulation areas. Linear design with opal diffuser for high uniformity, ensuring homogeneous light distribution while minimizing shadows and glare. Pass-through wiring and double connector included, allowing for continuous runs of up to 10 luminaires per line. Installation type: Surface. Optics: 120. Color temperature: 5500K. Power: 36W. Lumens: 3600lm. Efficiency: 100lm/w. Protection rating IP: IP65. Power supply: 220-240 V. 50/60 Hz. Dimensions: 1265 mm x 65 mm x 65 mm.

APPLICATION

Parking, Industrial
lighting, General lighting, Car
park lighting

TECHNICAL INFORMATION

FREQUENCY

50 - 60 Hz

IK CLASSIFICATION

08

IP RATING

IP65

OPERATING TEMPERATURE RANGE (°C)

-25...+40

POWER SUPPLY (V~)

220/240 V~

CONTROL

On/Off

LIGHTING EFFICIENCY (LM/W)

100 lm/W

LUMENS (LM)

3600 lm

OPTICS

General

POWER (W)

36 W

INSTALLATION AND MAINTENANCE

INSTALLATION TYPE

Surface / Wall

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053440278

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.85

PRODUCT NET WEIGHT

0.76

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053440278

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

225

PACKAGING WIDTH

300

PACKAGING LENGTH

1320

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

89100000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

10.2

PACKAGING NET WEIGHT

0.76

PACKAGING WEIGHT UNIT

KGM