

German socket outlet 16A 250V~ with safety device and 1Click® terminal connection white Simon 500 Cima

REF. 50000432-030



BASIC INFORMATION

DESCRIPTION

Versatility, functionality and innovation in the Schuko double socket outlet of the collection Simon 500 Cima. With a classic and white tones tone, this double socket outlet with power supplies is compatible with a voltage of 250 Volts, and 16 Amps and can reach to reach temperatures of more than 60 °C. Composed of metal materials isolated with self-extinguishing halogen-free thermoplastic, protects the room in case of fire, to prevent the flame spread and toxicity by smoke. With a size of 100 x 50 mm and a depth of 46 mm, its installation is suitable for recessed or surface-mounted, with security included and quick terminal connection by click, without the need for stripping cabling. With this installation is reduces the time of the assembly in a 50% since only have to insert, tighten and enjoy a product already installed.

FINISH

White

PACKAGING CONTENTS

Double socket outlet with cover and installation manual

ETIM CLASS

EC000125

COMPATIBILITY

Simon 500 Cima enclosures

REMARKS

Possibility to order replacement cover in case of breakage, with article no.50001841-030

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

CABLE SECTION ADMITTED (MM)

From 1,5 to 2,5 mm

AVAILABLE IN

German and French format

NUMBER OF CONNECTIONS PER TERMINAL

1 terminal connection for click terminal connection system and 2 terminal connections for screw terminal connection system

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

FORMAT

Schuko

HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

INDICATOR FUNCTION

No

INSULATION RESISTANCE (V-MΩ)

>5MΩ at 500V

CURRENT (A)

16 A

IP RATING

IP20

KIT AVAILABILITY

No

LINKABLE

Yes, using accessory 50000996-039

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-25 to 60 °C

TYPE OF MECHANISM

Insertion

NUMBER OF MODULES

2

MONOBLOCK

No

RAL

9003

NUMBER OF SOCKETS

2

VERSION

Double

VOLTAGE (V~)

250 V~

INSTALLATION AND MAINTENANCE

CABLE STRIPPING NECESSARY (MM)

0

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX

Specific Simon 500 Cima

REMOVAL OF THE SOCKET

Only with tool

REMOVAL OF COVER

Only with tool

INSTALLATION DIRECTION

Horizontal, Vertical

TYPE OF TERMINAL

CONNECTION - FUNCTION 1

1 click connection (1 click®)

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-10-2)

INSTALLATION TYPE

Suitable for surface and flush mounting

NUMBER OF TERMINALS

3 inputs and 3 outputs

REGULATIONS

REGULATIONS

Dir. 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | IEC 60884-1 Ed. 3.2 | UNE 20315-1-1:2017 | UNE 20315-1-2:2017 | DS 60884-2-D1:2023

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053254561

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.109

PRODUCT NET WEIGHT

0.109

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053093139

UNITS CONTAINED PACKAGING

10

PACKAGING HEIGHT

112

PACKAGING WIDTH

117

PACKAGING LENGTH

269

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3.525

PACKAGING VOLUME UNIT

DMQ

PACKAGING GROSS WEIGHT

0

PACKAGING NET WEIGHT

1.09

PACKAGING WEIGHT UNIT

KGM

