Voice and data flat plate without dust cover for 1 element for 2 3M® RJ45 connectors black Simon K45

REF. **KB045/14**



BASIC INFORMATION

DESCRIPTION

This flat base plate of voice and data consists of 1 element for 2 connectors RJ45 from 3M ®. Does not include dust shutter and is finished in black colour, measuring 45x45 mm and a depth of 8.5 mm, it is in the series Simon K45. Its manufacturing material is halogen-free thermoplastic, which guarantees that the fire is not propagate in the case of a notional fire, and low toxicity if any smoke. The piece complies with the regulation and is designed for both surface and flush mounting. In this type of articles, maintenance is very important. It is ideal to clean the plate with a soft, dry cloth and avoid abrasive cleaners containing chlorine. The collection Simon K45 lands with the aim of improve the workplace solutions of the spaces through functional mechanisms and adapted to the current needs.

FINISH

Black

COMPATIBILITY

Simon K45 enclosures for installation in the wall, floor, ceiling and furniture and Simon 500 Cima enclosures (need to be combined with the K45 to 500 Cima adaptor ref.50012088-038)

PACKAGING CONTENTS

Flat voice and data plate without dust cover

ETIM CLASS

EC000018

REMARKS

When combining the voice and data plate in vertical housings (mini columns, columns, Teleblock, channels, mechanism holders, etc.) you must use the 90º positioner (ref. K66) to guide the plate into a vertical position.

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

COMPATIBLE WITH CONNECTORS
Volition OCK®, RJ45, K5e and K6 from 3M®.

RJ45 CONNECTORS
Not included in voice and data plate

MAX TEMP DURING CONSTRUCTION WORK (°C)
+60° C

DUST PROTECTION
No

FORMAT
RJ45

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)
-5 to 60° C

NUMBER OF MODULES
Half

PLATE TYPE
Flat

RAL
7021

RJ45 ADAPTOR MODULE
Included in voice and data plate

SNAP-FIT RJ45 PLATES
3M® RJ45 connectors

SNAP-FIT TYPE
3M® RJ45 connectors

VERSION
Single

INSTALLATION AND MAINTENANCE

INSTALLABLE IN FLUSH MOUNT JUNCTION BOX
Universal, specific Simon K45 and specific Simon 500 Cima using adaptor (ref.50012088-038)

INSTALLATION DIRECTION
Vertical according to the direction of the mechanisms

INSTALLATION TYPE
Suitable for surface and flush mounting

REMOVAL OF THE PLATE
Only with tool

REGULATIONS

REGULATIONS
Directive 2011/65/UE RoHS + post. mod. | EN IEC 63000:2018 | EN 50173-1:2018*1

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0.3

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.013

PRODUCT NET WEIGHT
0.013

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8426436040052

UNITS CONTAINED PACKAGING
20

PACKAGING HEIGHT
70

PACKAGING WIDTH
93

PACKAGING LENGTH
140

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
911400

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.28

PACKAGING NET WEIGHT
0.26

PACKAGING WEIGHT UNIT
KGM