

Hinged cover for adjustable floor box or service cover in concrete or raised floor for 8 elements grey Simon 500 Cima

REF. RSF004/1



BASIC INFORMATION

DESCRIPTION

With measures of 160x256x15 mm, our hinged cover 8 elements in grey colour, we can use both for adjustable floor box, to register in concrete or raised floor to our. The piece is manufactured with metal components with self-extinguishing thermoplastic insulation coated fully halogen-free to ensure that in case of fire is no flame spread, in addition to a toxicity very low if had any smoke. For this reason, the collection Simon 500 Cima manages to assemble the safest mechanisms on the market for those who do not wish to renouncing the hallmark of guarantee of one of the most dedicated in the sector, and that is that Simon is one of the most so by always offer the most innovative products to meet to its customers the most demanding.

FINISH

Grey

PACKAGING CONTENTS

Hinged cover

MATERIAL

Plastic

ETIM CLASS

EC001903

REMARKS

The adjustable floor boxes include the hinged cover. Only necessary to order it as a replacement part in the event of breakage or loss.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS

No

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS

Yes, thanks to the inclusion of protective foam

AVAILABLE IN

2, 4, 6, 8 and 12 elements

DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

MAX TEMP DURING CONSTRUCTION WORK (°C)

+90 °C

HEAT RESISTANCE (°C)

+125°C (according rule IEC 60695-10-2)

INSULATION RESISTANCE (V-MΩ)

>5 MOhms at 500V

KIT AVAILABILITY

Yes

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

NUMBER OF MODULES

8 modules

RAL

7011

VERSION

8 elements

INSTALLATION AND MAINTENANCE

REMOVAL OF COVER

Only with tool

EXTINGUISHING (°C)

+850 °C / 30 seconds (GWFI in accordance with standard IEC 60695-2-11)

TYPE OF FASTENING

Via coupling pin supplied on the cover

INSTALLATION DIRECTION

Horizontal, Vertical

INSTALLATION TYPE

In raised or concrete floor with adjustable floor boxes or service covers

REGULATIONS

REGULATIONS

UNE-EN 60.670-23

LOGISTICS INFORMATION

UNITARY EAN CODE

8426436056237

UNITARY PACKAGING WEIGHT
UNIT

KGM

PACKAGING MEASUREMENT
UNIT

MMT

UNITARY PACKAGING HEIGHT

0

PACKAGING EAN

8426436056237

PACKAGING VOLUME

1.75

UNITARY PACKAGING WIDTH

0

UNITS CONTAINED PACKAGING

1

PACKAGING VOLUME UNIT

DMQ

UNITARY PACKAGING LENGTH

0

PACKAGING HEIGHT

20

PACKAGING GROSS WEIGHT

0

UNITARY PACKAGING VOLUME

0

PACKAGING WIDTH

350

PACKAGING NET WEIGHT

0.913

UNITARY PACKAGING GROSS
WEIGHT

0.913

PACKAGING LENGTH

250

PACKAGING WEIGHT UNIT

KGM

PRODUCT NET WEIGHT

0.913