Kit Flash 90 consisting of british modular power socket, USB Type C Dock including 1x HDMI + LAN + 3x USB Type A, USB charger Type C 20W and grommet (cable outlet) black Simon K45

REF. **KR3341301/14**



BASIC INFORMATION

DESCRIPTION

Kit Flash 90 based on a modular british power socket-outlet for installation in furniture with an optional protective lid to allow it to be closed and hide the connections when not in use. Includes a USB Type-C dock with 1 HDMI output for display, 1 Gigabit Ethernet port, and 3 USB Type-A connectors for keyboard, mouse, and any other connection device based on the USB Type-A connector. The kit includes a 20W USB Type-C charger and a cable outlet in a black finish. Supplied with a 20cm long patch cable terminated in a 3-pole Wieland® Gst18i male aerial quick connector with a safety anchor to facilitate safe connection and disconnection from the mains without interrupting the power supply. The kit is supplied assembled with the internal connections pre-made. It is only necessary to make the die in the furniture where the product will be fixed and once done, connect it to the mains for it to be functional. It requires ordering the dock power supply separately (ref. CR6100121150201/14)

FINISH

Black

MATERIAL

Plastic

ETIM CLASS

EC002759

TECHNICAL INFORMATION

AVAILABLE MARKET
CE

PROTECTION AGAINST DIRECT ACCESS OF CONTACTS
Yes

PROTECTION AGAINST ENTRY OF DUST AND SMALL OBJECTS
Protective lid available (as an option) to protect the connections against entry of dust and small objects

RJ45 CONNECTORS
Yes

CONNECTOR TYPE
British

NUMBER OF CONTACTS
3

FORMAT
British

CURRENT (A)
13 A

IP RATING
IP20

MAINTENANCE
Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

NOMINAL VOLTAGE (V~)
250 V~

RAL
9005

RECESS DIMENSION (MM)
ø80 mm

RJ45 ADAPTOR MODULE
Yes

SNAP-FIT RJ45 PLATES
Directly to the Dock

SNAP-FIT TYPE
Embedded in the dock

USB CHARACTERISTICS
Charging

USB CURRENT (A)
2,2 A

POWER DELIVERY USB
Yes

QUICK CHARGE USB
Yes

USB VOLTAGE (V~)
9 V~

VOLTAGE (V~)
250 V~

INSTALLATION AND MAINTENANCE

REMOVAL OF COMPONENTS
No tools needed

REMOVAL OF COVER
Only with tool

EXTINGUISHING (°C)
+650 °C (according to standard IEC 60670)

REGULATIONS

REGULATIONS

Dir. 2014/35/UE LVD*1 | Dir. 2014/30/UE EMC*3 |Dir. 2011/65/UE RoHS + post. mod.*1 | Dir. 2009/125/EC ErP (Reg. UE 2019/1782) *1 *13 *12 | S.I. 2016 No. 1101 - The Electrical Equipment (Safety) Regulations 2016*2 | S.I. 2012 No. 3032 - The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012*2 | IEC 60884-1 Ed.3.2*1 | BS 1363-2:2016+A1:2018*2 | UNE 20315-1-1:2017*5 | BS 1363-4:2016+A1:2018*2 | UNE 20315-1-2:2017*5 | DS 60884-2-D1:2023*4 | CEI 23-50 V4*7 | SANS 164-1:2021*6 | SN 441011-2-1:2019*9 | SI 32 Fig. 204 B*8 | AS/NZS 3112:2017*11 | EN 50173-1:2018*10 | EN 50563:2011 + A1:2013*13 *12 | EN 55032:2015 + A11:2020 + A1:2020*12*14 *16 | EN 62368-1: 2014 + A11:2017*13 *12 | EN 55035:2017 + A11:2020*12*14 *16 | ETSI-EN 301489-34 V2.1.1*13 | EN IEC 61000-3-2:2019 + A1:2021 + A2:2024*12 *16 | EN IEC 60670-1:2021+ A11:2021*15 | EN 61000-3-3:2013 +A1:2019 + A2:2021 *12 *16 | EN IEC 63000:2018

LOGISTICS INFORMATION

UNITARY EAN CODE
8421053398302

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING VOLUME UNIT
MMQ

UNITARY PACKAGING GROSS WEIGHT
0.793

PRODUCT NET WEIGHT
0.633

UNITARY PACKAGING WEIGHT UNIT
KGM

PACKAGING EAN
8421053398302

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
120

PACKAGING WIDTH
130

PACKAGING LENGTH
252

PACKAGING MEASUREMENT UNIT
MMT

PACKAGING VOLUME
3931200

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0.793

PACKAGING NET WEIGHT
0.633

PACKAGING WEIGHT UNIT
KGM