

L connector with exterior ground adjustable 3-phase rail White

REF. 99940730-039



BASIC INFORMATION

APPLICATION

Domestic,Office,Retail,Contract

PACKAGING CONTENTS

1 Unit

TECHNICAL INFORMATION

OPERATING TEMPERATURE RANGE (°C)

0 - 35 °C

CONTROL

1-10 V

DRIVER INCLUDED

No

RAL

9016

DIRECTIONAL

No

ENERGY EFFICIENCY

A+

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Flush-mounted

INSTALLATION TYPE

Surface-mounted / Flush-mounted

REGULATIONS

EAC MARKED

No

ECORRAE MARKED

No

WARRANTY

3 years

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
0

UNITARY PACKAGING WIDTH
0

UNITARY PACKAGING LENGTH
0

UNITARY PACKAGING VOLUME
0

UNITARY PACKAGING GROSS
WEIGHT
0

PRODUCT NET WEIGHT
0

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING EAN
8436547037520

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
0

PACKAGING WIDTH
0

PACKAGING LENGTH
0

PACKAGING MEASUREMENT
UNIT
MMT

PACKAGING VOLUME
0

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
0

PACKAGING NET WEIGHT
0

PACKAGING WEIGHT UNIT
KGM