

## Module for 1 RJ45 R&M® in angled voice and data plates

REF. MD54



### BASIC INFORMATION

#### DESCRIPTION

It belongs to the Simon 500 Cima series, and is a product is ideal for connector, 1 R & M ® RJ45 in angled voice and data plates of the same series of Simon products. The module is installed in a very simple and measures 32 x 20 millimetres and 10 millimetres of depth. Simon uses the best materials in the manufacture of their products, always with the aim of convert it into highly functional to technical level, as well as durable over time. In this case, the module is manufactured with halogen-free thermoplastic material, the latest in the market technology. This material is highly resistant and provides an extra hardness the product, so this is susceptible to withstand challenges external as knocks or scratches without visible due to its good operation. In addition, it can withstand temperatures also high or very low between -5 and 60 degrees centigrade. To be thermoplastic insulation, also contributes to the no-propagation of the spread in case of fire and reduces the toxicity of smoke, if this is producing. For this reason, the module, and the set in general it is highly secure.

#### COMPATIBILITY

Simon 500 Cima and Simon K45 angled voice and data plates

#### PACKAGING CONTENTS

MD Module for 1 RJ45

#### ETIM CLASS

EC002948

#### REMARKS

The MD Module can only be combined with angled voice and data plates (flat voice and data plates include the MD Module on the plate itself).

## TECHNICAL INFORMATION

### AVAILABLE IN

MD Module for 1 RJ45

### COMPATIBLE WITH CONNECTORS

Classic series Cat5e (R925371, R925370), Star Cat6 series (R302373, R302372) and Advanced Cat6A series (R509500, R509504) from R&M® (Reichle de Massari®).

### RJ45 CONNECTORS

Not included in the MD Module

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60 °C

### FORMAT

RJ45

### KIT AVAILABILITY

No

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 to 60 °C

### SNAP-FIT RJ45 PLATES

RJ45 R&M® connectors

### SNAP-FIT TYPE

RJ45 R&M® connectors

## INSTALLATION AND MAINTENANCE

### INSTALLATION DIRECTION

Vertical, corresponding with the MD Module fastening slots

### INSTALLATION TYPE

Fixing by direct snap-fit, no tools needed.

## REGULATIONS

### REGULATIONS

UNE-EN 60.670-1:2006

## LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT 0	PRODUCT NET WEIGHT 0.002	PACKAGING MEASUREMENT UNIT MMT
UNITARY PACKAGING WIDTH 0	UNITARY PACKAGING WEIGHT UNIT KGM	PACKAGING VOLUME 544320
UNITARY PACKAGING LENGTH 0	PACKAGING EAN 8426436037885	PACKAGING VOLUME UNIT MMQ
UNITARY PACKAGING VOLUME 0.3	UNITS CONTAINED PACKAGING 50	PACKAGING GROSS WEIGHT 0.1
UNITARY PACKAGING VOLUME UNIT MMQ	PACKAGING HEIGHT 72	PACKAGING NET WEIGHT 0.1
UNITARY PACKAGING GROSS WEIGHT 0.002	PACKAGING WIDTH 72	PACKAGING WEIGHT UNIT KGM
	PACKAGING LENGTH 105	