

Downlight 725.26 WW Comfort

REF. 72526030-883



BASIC INFORMATION

APPLICATION

Accent lighting, General lighting

PACKAGING CONTENTS

1 unit

ETIM CLASS

EC001744

TECHNICAL INFORMATION

IP RATING

IP44

DRIVER INCLUDED

Yes

LUMENS (LM)

1300 lm

OPERATING TEMPERATURE RANGE (°C)

-10 - 35 °C

L70 (°C)

30,000 h

LUMENS/W

1300 lm/14W

COLOR TEMPERATURE (K)

3000 K

LIGHT BEAM APERTURE ANGLE (°)

120°

OPTICS

General

CONTROL

On/Off

COLOR TYPE

WW

PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

CRI

80

LIGHTING EFFICIENCY (LM/W)

92,9 lm/W

POWER (W)

14 W

CHROMATICS CRI ICONS

CRI
80

INSTALLATION AND MAINTENANCE

INSTALLATION ALTERNATIVES

Surface-mounted

INSTALLATION TYPE

Flush-mounted

REGULATIONS

WARRANTY

3 years

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053089712

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.685

PRODUCT NET WEIGHT

0.481

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053089712

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

100

PACKAGING WIDTH

185

PACKAGING LENGTH

175

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

3237500

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.685

PACKAGING NET WEIGHT

0.481

PACKAGING WEIGHT UNIT

KGM