

Modular luminaire 726 60x60 Low Glare 3000K 1-10V 5Y

REF. 72680133-683



BASIC INFORMATION

APPLICATION

General lighting, Office

ETIM CLASS

EC002892

TECHNICAL INFORMATION

IP RATING

IP20

COLOR TEMPERATURE (K)

3000 K

CRI

80

L70 (°C)

36.000 h a 25°C

LIGHT BEAM APERTURE ANGLE (°)

90°

LIGHTING EFFICIENCY (LM/W)

91,28 lm/W

LUMENS (LM)

3560 lm

OPTICS

Batwing 105°

PHOTOBIOLOGICAL CLASSIFICATION

Exempted category

POWER (W)

39 W

SERVICE LIFE

50.000 h

CHROMATICS CRI ICONS

CRI
80

LOGISTICS INFORMATION

UNITARY PACKAGING HEIGHT
60

UNITARY PACKAGING WIDTH
740

UNITARY PACKAGING LENGTH
640

UNITARY PACKAGING
MEASUREMENT UNIT
MMT

UNITARY PACKAGING VOLUME
28416000

UNITARY PACKAGING VOLUME
UNIT
MMQ

UNITARY PACKAGING GROSS
WEIGHT
3

PRODUCT NET WEIGHT
2.8

UNITARY PACKAGING WEIGHT
UNIT
KGM

PACKAGING EAN
8421053285824

UNITS CONTAINED PACKAGING
1

PACKAGING HEIGHT
60

PACKAGING WIDTH
740

PACKAGING LENGTH
640

PACKAGING MEASUREMENT
UNIT
MMT

PACKAGING VOLUME
28416000

PACKAGING VOLUME UNIT
MMQ

PACKAGING GROSS WEIGHT
3

PACKAGING NET WEIGHT
2.8

PACKAGING WEIGHT UNIT
KGM