

Custom button box 1 function for temperature control cold aluminium Simon 82 Sense

REF. 8000615-093



BASIC INFORMATION

FINISH

Matt aluminium

MATERIAL

Thermoplastic

PACKAGING CONTENTS

Keypad and instructions

REMARKS

Requires installation on LON or KNX bus coupling unit (8000100-039 or 8400100-039). Possibility of customising and creating your own configuration by choosing the functions you need from our icon library.

TECHNICAL INFORMATION

AVAILABLE MARKET

CE

IP RATING

IP20

TYPE OF MECHANISM

Touch

NUMBER OF POSSIBLE ELEMENTS

1 element

MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

OPERATING TEMPERATURE RANGE (°C)

0 - 45 °C

INDICATOR FUNCTION

Yes

POWER SUPPLY (V~)

24 Vdc

INSTALLATION AND MAINTENANCE

BUS CONNECTION TYPE OF TERMINAL CONNECTION

Por inserción

INSTALLATION TYPE

Suitable for surface and flush mounting

TYPE OF TERMINAL CONNECTION - FUNCTION 1

Fast

REGULATIONS

REGULATIONS

Directive 2014/35/UE LVD + Directive 2014/30/UE EMC + Directive 2011/65/UE RoHS + EN 50581:2012 + EN 60669-2-5:2016

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053128428

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING GROSS WEIGHT

0.04

PRODUCT NET WEIGHT

0.04

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053128428

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

26

PACKAGING WIDTH

58

PACKAGING LENGTH

86

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

129.688

PACKAGING VOLUME UNIT

CMQ

PACKAGING GROSS WEIGHT

0.04

PACKAGING NET WEIGHT

0.04

PACKAGING WEIGHT UNIT

KGM