

PD-4x4 Slim PIR+LUX recessed box DALI-2 Input white IP20

REF. 89219310-230



BASIC INFORMATION

DESCRIPTION

PIR presence and brightness detector for flush mounting. The recommended installation height is 2.8 m, with a maximum height of 4 m. It has a detection angle of 360 ° and an opening angle of 71 °. The tangential detection range is 4 x 4 m and the radial detection range is 4 x 4 m.

The brightness regulation range is 10 - 1000 lux. The detector configuration is done through DALI.

It features TEACH operating mode. Possibility of interconnection between sensors via DALI. The control protocol is DALI-2 Input. The typical consumption is 4 mA.

The power supply voltage is DALI (12 - 20.5 VDC). The operating temperature of the detector is: 0 - 40 °C. White finish, IP 20 protection rating, and dimensions: 80 x 80 x 50 mm.

5-year warranty

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

ETIM CLASS

EC001582

TECHNICAL INFORMATION

IP RATING

IP20

RAL

9010

POWER SUPPLY (V~)

DALI bus (12 Vdc – 20,5 Vdc)

CONTROL

DALI2 Slave

INSTALLATION AND MAINTENANCE

MINIMUM INSTALLATION HEIGHT

2.5

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053343135

UNITARY PACKAGING HEIGHT

0

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING LENGTH

0

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING VOLUME

0

UNITARY PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING GROSS WEIGHT

0.133

PRODUCT NET WEIGHT

0.043

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING EAN

8421053343135

UNITS CONTAINED PACKAGING

1

PACKAGING HEIGHT

130

PACKAGING WIDTH

90

PACKAGING LENGTH

90

PACKAGING MEASUREMENT UNIT

MMT

PACKAGING VOLUME

1053000

PACKAGING VOLUME UNIT

MMQ

PACKAGING GROSS WEIGHT

0.133

PACKAGING NET WEIGHT

0.043

PACKAGING WEIGHT UNIT

KGM