

## Customisable table-top kit with 2xUSB charger, 3 German socket outlets and 1 empty element aluminium Simon 400

REF. 42523000-133



### BASIC INFORMATION

#### FINISH

Aluminium

#### MATERIAL

Metal

#### COMPATIBILITY

Functions of the Simon 400 range, combinable with the Simon Electric Cabling range.

#### PACKAGING CONTENTS

Pre-wired profile, table-top supports, rear trim cover and installation manual.

#### ETIM CLASS

EC002759

#### REMARKS

To complete the product installation combine it with the Simon 400 functions (refs. 400XXXXX-03X).

## TECHNICAL INFORMATION

### AVAILABLE MARKET

CE

### INSULATION RESISTANCE (V-MΩ)

>5 M? at 500 V

### RAL

9006

### DIELECTRIC STRENGTH

No holes or contours, with 2000V at 50 Hz for 1 minute

### CURRENT (A)

16 A

### NUMBER OF REAR ENTRANCES

1

### MAX TEMP DURING CONSTRUCTION WORK (°C)

+60◆C

### IP RATING

IP30

### NUMBER OF SOCKETS

3 sockets for standard current circuit

### NUMBER OF POSSIBLE ELEMENTS

1

### MAINTENANCE

Clean with a soft, dry cloth. Do not use abrasive cloths or cleaning products that contain chlorine.

### NUMBER OF USB CHARGERS

1

### FORMAT

Schuko

### TEMPERATURE RANGE DURING INSTALLATION (°C)

-5 at +60◆C

### VERSION

5 elements

### HEAT RESISTANCE (°C)

+70°C (according to standard IEC 60670)

### TYPE OF POWER SUPPLY CONNECTOR

Wieland◆ GST 18i male 3-pole overhead connector with 22 cm patch cord

### VOLTAGE (V~)

250 V~

## INSTALLATION AND MAINTENANCE

### CLAW RANGE OF OPERATION (MM)

Between 16 and 40 mm

### TYPE OF FASTENING

By tightening existing clamps in the fastening bracket.

### SECURING POSSIBILITIES

Using clips included in the fastening brackets

### REMOVAL OF COMPONENTS

### INSTALLATION TYPE

Suitable for fixing to furniture.

### MOUNTING WITHOUT ACCESSORIES

Supplied with all necessary materials for installation.

### EXTINGUISHING (°C)

+70 °C (according to standard IEC 60670)

### REMOVAL OF THE PLATE

Only with tool

## REGULATIONS

### REGULATIONS

Directiva 2014/35/UE LVD;Directiva 2011/65/UE RoHS;EN 50581:2012;EN 60670-1:2005;EN 60670-1:2005 A1:2013;IEC 60884-1 Ed 3.2;

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053208106

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

2.15

### PRODUCT NET WEIGHT

2.15

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053208106

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

90

### PACKAGING WIDTH

195

### PACKAGING LENGTH

320

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

5616000

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0

### PACKAGING NET WEIGHT

2.15

### PACKAGING WEIGHT UNIT

KGM