

## Downlight 703.25 2700 K Wide Flood IP65 Black

REF. 70325038-482



### BASIC INFORMATION

#### APPLICATION

Hotel,Wet  
areas,Restaurants,Residential,Retail,Office,Healthcare,Education

#### PACKAGING CONTENTS

1 unit

#### ETIM CLASS

EC001744

## TECHNICAL INFORMATION

### FREQUENCY

50 - 60 Hz

### CRI

80

### LUMENS (LM)

680 lm

### IP RATING

IP65

### CUT OFF

No

### LUMENS/W

680 lm/7.5 W

### OPERATING TEMPERATURE RANGE (°C)

15 - 35 °C

### DRIVER INCLUDED

Yes

### OPTICS

Wide Flood

### POWER SUPPLY (V~)

230 V~

### L70 (°C)

30,000 h at 25 °C

### PHOTOBIOLOGICAL CLASSIFICATION

Exempt category

### COLOR TEMPERATURE (K)

2700 K

### LIGHT BEAM APERTURE ANGLE (°)

40°

### POWER (W)

7.5 W

### CONTROL

On/Off

### LIGHTING EFFICIENCY (LM/W)

91 lm/W

### SERVICE LIFE

30.000 h

### CHROMATICS CRI ICONS

CRI  
80

## INSTALLATION AND MAINTENANCE

### INSTALLATION TYPE

Flush-mount

## REGULATIONS

### WARRANTY

3 years

## LOGISTICS INFORMATION

### UNITARY EAN CODE

8421053089309

### UNITARY PACKAGING HEIGHT

0

### UNITARY PACKAGING WIDTH

0

### UNITARY PACKAGING LENGTH

0

### UNITARY PACKAGING VOLUME

0

### UNITARY PACKAGING GROSS WEIGHT

0.32

### PRODUCT NET WEIGHT

0.2

### UNITARY PACKAGING WEIGHT UNIT

KGM

### PACKAGING EAN

8421053089309

### UNITS CONTAINED PACKAGING

1

### PACKAGING HEIGHT

110

### PACKAGING WIDTH

135

### PACKAGING LENGTH

170

### PACKAGING MEASUREMENT UNIT

MMT

### PACKAGING VOLUME

2524500

### PACKAGING VOLUME UNIT

MMQ

### PACKAGING GROSS WEIGHT

0.32

### PACKAGING NET WEIGHT

0.2

### PACKAGING WEIGHT UNIT

KGM