

Multisensor Aerosol recessed box KNX white IP20

REF. 89232710-230



BASIC INFORMATION

DESCRIPTION

Multisensor aerosol. The recommended installation height is - m, with a maximum height of - m. It has a detection angle of . The tangential detection range is - m and the radial detection range is - m. The luminosity regulation range is . The detector configuration is done through a bluetooth application and KNX. It has a TEACH operating mode. Possibility of interconnection between sensors via KNX. The control protocol is KNX. The typical consumption is 15 mA. The power supply voltage is KNX (21 - 30 VDC). The operating temperature of the detector is: 0 - 40 °C. White finish, protection grade IP 20 and dimensions: 123 x 123 x 33 mm. 5-year warranty.

For more product information, visit STEINEL website by clicking [here](#)

FINISH

White

COMPATIBLE WITH MECHANICAL PUSH BUTTON

No

TECHNICAL INFORMATION

IP RATING

IP20

RAL

9003

POWER SUPPLY (V~)

Bus KNX (21 Vcc...32 Vcc)

CONTROL

KNX

LOGISTICS INFORMATION

UNITARY EAN CODE

8421053380581

UNITARY PACKAGING GROSS WEIGHT

0.26

PACKAGING LENGTH

162

UNITARY PACKAGING HEIGHT

0

PRODUCT NET WEIGHT

0.156

PACKAGING MEASUREMENT UNIT

MMT

UNITARY PACKAGING WIDTH

0

UNITARY PACKAGING WEIGHT UNIT

KGM

PACKAGING VOLUME

2325323

UNITARY PACKAGING LENGTH

0

PACKAGING EAN

8421053380581

PACKAGING VOLUME UNIT

MMQ

UNITARY PACKAGING MEASUREMENT UNIT

MMT

UNITS CONTAINED PACKAGING

1

PACKAGING GROSS WEIGHT

0.26

UNITARY PACKAGING VOLUME

0

PACKAGING HEIGHT

142

PACKAGING NET WEIGHT

0.156

UNITARY PACKAGING VOLUME UNIT

MMQ

PACKAGING WIDTH

100

PACKAGING WEIGHT UNIT

KGM